



## CANOPY 100W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- \* WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- \* HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, GAS STATION, HALL MEETING ETC.



### SPECIFICATION

TUBE MATERIAL	: Aluminum + Glass
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 100W
LUMINOUS FLUX	: >11000 lm
EFFICACY	: >110lm/W
COLOR RENDERING INDEX	: 70/80
LED COLOR TEMPERATURE	: 2700-6500K $\pm$ 500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		HOLE CUT(mm)		WEIGH	REMARK
	WATT	TYPE	W	H	g	
XZ-GS-B	100	SMD LED	382	382	5.5	



## CANOPY 150W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- \* WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- \* HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, GAS STATION, HALL MEETING ETC.



### SPECIFICATION

TUBE MATERIAL	: Aluminum + Glass
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 150W
LUMINOUS FLUX	: 16500 lm
EFFICACY	: >110 lm/W
COLOR RENDERING INDEX	: 70/80
LED COLOR TEMPERATURE	: 2700-6500K $\pm$ 500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		HOLE CUT(mm)		WEIGH	REMARK
	WATT	TYPE	W	H	g	
XZ-GS-B	150	SMD LED	382	382	5.5	