



## LED DOWNLIGHT 6W 023B

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , EPISTAR
POWER	: 6W
LUMINOUS FLUX	: 480lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	Ø	H	
XZ-023-6W	6	SMD	120	40	



## LED DOWNLIGHT 12W 023B

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , EPISTAR
POWER	: 12W
LUMINOUS FLUX	: 960lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	Ø	H	
XZ-023-12W	12	SMD	172	40	



## LED DOWNLIGHT 18W 023B

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , EPISTAR
POWER	: 18W
LUMINOUS FLUX	: 1440lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	Ø	H	
XZ-023-18W	18	SMD	225	40	



## LED DOWNLIGHT 24W 023B

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , EPISTAR
POWER	: 24W
LUMINOUS FLUX	: 1920lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	Ø	H	
XZ-023-24W	24	SMD	300	40	