



LED DOWNLIGHT 3W B30

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 3W
LUMINOUS FLUX	: 240lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

- TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
- RADIO DISTURBANCE LIMITS
- ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
- RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-B30-3W	3	SMD	90	90	25	CUTOUT 72x72 mm.



LED DOWNLIGHT 6W B30

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY
AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 6W
LUMINOUS FLUX	: 480lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-B30-6W	6	SMD	120	120	25	CUTOUT 100x100 mm.



LED DOWNLIGHT 9W B30

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 9W
LUMINOUS FLUX	: 720lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-B30-9W	9	SMD	150	150	25	CUTOUT 130x130 mm.



LED DOWNLIGHT 12W B30

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 12W
LUMINOUS FLUX	: 960lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

- TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
- RADIO DISTURBANCE LIMITS
- ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
- RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-B30-12W	12	SMD	170	170	25	CUTOUT 150x150 mm.



LED DOWNLIGHT 15W B30

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 15W
LUMINOUS FLUX	: 1200lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°c
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

- TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
- RADIO DISTURBANCE LIMITS
- ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
- RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-B30-15W	15	SMD	195	195	25	CUTOUT 175x175 mm.



LED DOWNLIGHT 18W B30

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 18W
LUMINOUS FLUX	: 1440lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°c
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

- TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
- RADIO DISTURBANCE LIMITS
- ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
- RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-B30-18W	18	SMD	225	255	25	



LED DOWNLIGHT 24W B30

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 24W
LUMINOUS FLUX	: 1920lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

- TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
- RADIO DISTURBANCE LIMITS
- ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
- RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-B30-24W	24	SMD	300	300	25	