



## LED DOWNLIGHT COB-15W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 15W
LUMINOUS FLUX	: 1300lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 38°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-15W	15	SMD	133	133	55	



## LED DOWNLIGHT COB-20W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 20W
LUMINOUS FLUX	: 1700lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 38°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-20W	20	SMD	133	133	55	



## LED DOWNLIGHT COB-35W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 35W
LUMINOUS FLUX	: 3000lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 38°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-35W	35	SMD	133	133	55	



## LED DOWNLIGHT COB-50W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 50W
LUMINOUS FLUX	: 4200lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 38°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-50W	50	SMD	133	133	55	