



LED DOWNLIGHT COB 6W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 6W
LUMINOUS FLUX	: 550lm
EFFICACY	: >90lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-6W	6	SMD	90	90	78	



LED DOWNLIGHT COB 9W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 9W
LUMINOUS FLUX	: 800lm
EFFICACY	: >90lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

- TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
- RADIO DISTURBANCE LIMITS
- ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
- RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-9W	9	SMD	90	90	78	



LED DOWNLIGHT COB 15W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 15W
LUMINOUS FLUX	: 1300lm
EFFICACY	: >90lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-15W	15	SMD	109	109	77	



LED DOWNLIGHT COB 20W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 20W
LUMINOUS FLUX	: 1700lm
EFFICACY	: >90lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-20W	20	SMD	138	138	95	



LED DOWNLIGHT COB 25W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 25W
LUMINOUS FLUX	: 2200lm
EFFICACY	: >90lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

- TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
- RADIO DISTURBANCE LIMITS
- ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
- RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-25W	25	SMD	138	138	95	



LED DOWNLIGHT COB 35W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 35W
LUMINOUS FLUX	: 3000lm
EFFICACY	: >90lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 24°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

- TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
- RADIO DISTURBANCE LIMITS
- ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
- RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-35W	35	SMD	160	160	95	