



LED DOWNLIGHT COB-V 15W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY
AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE , EPISTAR , CITIZEN
POWER	: 15W
LUMINOUS FLUX	: 1200lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 80°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-15W-V	15	SMD	110	110	53	HOLE CUT : 95 mm.



LED DOWNLIGHT COB-V 20W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE , EPISTAR , CITIZEN
POWER	: 20W
LUMINOUS FLUX	: 1600lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 80°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-20W-V	20	SMD	145	145	69	HOLE CUT : 125-130 mm.



LED DOWNLIGHT COB-V 30W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE , EPISTAR , CITIZEN
POWER	: 30W
LUMINOUS FLUX	: 2400lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 80°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-30W-V	30	SMD	190	190	86	HOLE CUT : 165-170 mm.



LED DOWNLIGHT COB-V 40W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE , EPISTAR , CITIZEN
POWER	: 40W
LUMINOUS FLUX	: 3200lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 80°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-COB-40W-V	40	SMD	230	230	99	HOLE CUT : 200-210 mm.