



LED DOWNLIGHT 15W D001-2

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CITIZEN
POWER	: 15W
LUMINOUS FLUX	: 1050lm
EFFICACY	: 70-80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 24/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-D001-2-15W	15	SMD	140	260	144	



LED DOWNLIGHT 30W D001-2

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CITIZEN
POWER	: 30W
LUMINOUS FLUX	: 2400lm
EFFICACY	: 70-80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 24/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-D001-2-30W	30	SMD	160	320	163	



LED DOWNLIGHT 50W D001-2

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CITIZEN
POWER	: 50W
LUMINOUS FLUX	: 4016lm
EFFICACY	: 70-80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 24/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-D001-2-50W	50	SMD	190	375	173	



LED DOWNLIGHT 70W D001-2

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CITIZEN
POWER	: 70W
LUMINOUS FLUX	: 5600lm
EFFICACY	: 70-80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 24/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-D001-2-70W	70	SMD	203	425	188	