



## LED DOWNLIGHT 3W GUS

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 3W
LUMINOUS FLUX	: 240lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs



### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
RADIO DISTURBANCE LIMITS  
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	Ø CUTOUT	Ø	H	
XZ-B30-3W	3	SMD	70	80	25	



## LED DOWNLIGHT 6W GUS

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 6W
LUMINOUS FLUX	: 480lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10- 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	Ø CUTOUT	Ø	H	
XZ-B30-6W	6	SMD	100	120	25	



## LED DOWNLIGHT 9W GUS

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 9W
LUMINOUS FLUX	: 720lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
RADIO DISTURBANCE LIMITS  
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	Ø <sub>CUTOUT</sub>	Ø	H	
XZ-B30-9W	9	SMD	130	150	25	



## LED DOWNLIGHT 12W GUS

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 12W
LUMINOUS FLUX	: 960lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	Ø <sub>CUTOUT</sub>	Ø	H	
XZ-B30-12W	12	SMD	150	170	25	



## LED DOWNLIGHT 15W GUS

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY  
AND LONG DURATION TIMES

### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 15W
LUMINOUS FLUX	: 1200lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	Ø <sub>CUTOUT</sub>	Ø	H	
XZ-B30-15W	15	SMD	180	200	25	



## LED DOWNLIGHT 18W GUS

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 18W
LUMINOUS FLUX	: 1440lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-B30-18W	18	SMD	220	220	25	



## LED DOWNLIGHT 24W GUS

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PLASTIC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 24W
LUMINOUS FLUX	: 1920lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.



### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-B30-24W	24	SMD	300	300	25	