



## LED DOWNLIGH TD108-A-6W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 6W
LUMINOUS FLUX	: 350lm
EFFICACY	: <60lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD108-A-6W	6	SMD	90	90	56	HOLE CUT : 75 mm.



## LED DOWNLIGHT TD108-A-10W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 10W
LUMINOUS FLUX	: 700lm
EFFICACY	: >70-80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD108-A-10W	10	SMD	110	110	68	HOLE CUT : 90 mm.



## LED DOWNLIGH TD108-A-15W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 15W
LUMINOUS FLUX	: 1050lm
EFFICACY	: >70-80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD108-A-15W	15	SMD	138	138	82	HOLE CUT : 120 mm.



## LED DOWNLIGH TD108-A-20W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 20W
LUMINOUS FLUX	: 1760lm
EFFICACY	: >70-80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD108-A-20W	20	SMD	165	165	91	HOLE CUT : 135 mm.



## LED DOWNLIGH TD108-A-25W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 25W
LUMINOUS FLUX	: 2000lm
EFFICACY	: >70-80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD108-A-25W	25	SMD	195	195	107	HOLE CUT : 170 mm.



## LED DOWNLIGHT TD108-A-30W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 30W
LUMINOUS FLUX	: 2400lm
EFFICACY	: >70-80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD108-A-30W	30	SMD	235	235	128	HOLE CUT : 200 mm.