



LED DOWNLIGHT 7W TD88

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

| | |
|-----------------------|---------------|
| BODY MATERIAL | : ALUMINUM |
| INPUT VOLTAGE | : 180-260 VAC |
| LED CHIP | : SMD |
| POWER | : 7W |
| LUMINOUS FLUX | : 560lm |
| EFFICACY | : >80lm/W |
| COLOR RENDERING INDEX | : >80 |
| LED COLOR TEMPERATURE | : 2700-6000K |
| VIEW ANGLE | : 120° |
| THDi | : 15% |
| POWER FACTOR | : >0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : 50,000 hrs. |

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | REMARK |
|------------|------|------|-----------------|----|----|--------|
| | WATT | TYPE | W | L | H | |
| XZ-TD88-7W | 7 | SMD | 95 | 95 | 52 | |



LED DOWNLIGHT 10W TD88

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

| | |
|-----------------------|---------------|
| BODY MATERIAL | : ALUMINUM |
| INPUT VOLTAGE | : 180-260 VAC |
| LED CHIP | : SMD |
| POWER | : 10W |
| LUMINOUS FLUX | : 800lm |
| EFFICACY | : >80lm/W |
| COLOR RENDERING INDEX | : >80 |
| LED COLOR TEMPERATURE | : 2700-6000K |
| VIEW ANGLE | : 120° |
| THDi | : 15% |
| POWER FACTOR | : >0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : 50,000 hrs. |

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | REMARK |
|-------------|------|------|-----------------|-----|----|--------|
| | WATT | TYPE | W | L | H | |
| XZ-TD88-10W | 10 | SMD | 115 | 115 | 60 | |



LED DOWNLIGHT 13W TD88

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

| | |
|-----------------------|---------------|
| BODY MATERIAL | : ALUMINUM |
| INPUT VOLTAGE | : 180-260 VAC |
| LED CHIP | : SMD |
| POWER | : 13W |
| LUMINOUS FLUX | : 1000lm |
| EFFICACY | : >80lm/W |
| COLOR RENDERING INDEX | : >80 |
| LED COLOR TEMPERATURE | : 2700-6000K |
| VIEW ANGLE | : 120° |
| THDi | : 15% |
| POWER FACTOR | : >0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : 50,000 hrs. |

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | REMARK |
|-------------|------|------|-----------------|-----|----|--------|
| | WATT | TYPE | W | L | H | |
| XZ-TD88-13W | 13 | SMD | 140 | 140 | 65 | |



LED DOWNLIGHT 16W TD88

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

| | |
|-----------------------|---------------|
| BODY MATERIAL | : ALUMINUM |
| INPUT VOLTAGE | : 180-260 VAC |
| LED CHIP | : SMD |
| POWER | : 16W |
| LUMINOUS FLUX | : 1200lm |
| EFFICACY | : >80lm/W |
| COLOR RENDERING INDEX | : >80 |
| LED COLOR TEMPERATURE | : 2700-6000K |
| VIEW ANGLE | : 120° |
| THDi | : 15% |
| POWER FACTOR | : >0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : 50,000 hrs. |

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | REMARK |
|-------------|------|------|-----------------|-----|----|--------|
| | WATT | TYPE | W | L | H | |
| XZ-TD88-16W | 16 | SMD | 188 | 188 | 70 | |