



LED DOWNLIGHT TD-6W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING & PC COVER
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 6W
LUMINOUS FLUX	: 413lm
EFFICACY	: >70lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD-6W	6	SMD	100	100	51	HOLE CUT : 90 mm.

APPLICATION/DESCRIPTION

* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING & PC COVER
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 12W
LUMINOUS FLUX	: 840lm
EFFICACY	: >70lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD-12W	12	SMD	130	130	51	HOLE CUT : 120 mm.



LED DOWNLIGHT TD-15W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING & PC COVER
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 15W
LUMINOUS FLUX	: 1050lm
EFFICACY	: >70lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD-15W	15	SMD	160	160	52	HOLE CUT : 135 mm.



LED DOWNLIGHT TD-20W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING & PC COVER
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 20W
LUMINOUS FLUX	: 1600lm
EFFICACY	: >70lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD-20W	20	SMD	195	195	53	HOLE CUT : 175 mm.



LED DOWNLIGHT TD-30W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM HOUSING & PC COVER
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD , SANAN
POWER	: 30W
LUMINOUS FLUX	: 2000lm
EFFICACY	: >70lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 3000-6000K
VIEW ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-TD-30W	30	SMD	230	230	53	HOLE CUT : 210 mm.