



LED DOWNLIGHT TL-6W-081

APPLICATION/DESCRIPTION

* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

- BODY MATERIAL : ALUMINUM
- INPUT VOLTAGE : 180-260 VAC
- LED CHIP : CREE
- POWER : 6W
- LUMINOUS FLUX : 550lm
- EFFICACY : >80lm/W
- COLOR RENDERING INDEX : >80
- LED COLOR TEMPERATURE : 2700-5000K
- VIEW ANGLE : 15°/24°/38°
- THDi : 15%
- POWER FACTOR : >0.95
- WORKING TEMPERATURE : -10-50°C
- LIGHTING SOURCE LIFE : 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	D	H	
XZ-TL-6W-081	6	SMD	90	75	



LED DOWNLIGHT TL-7W-081

APPLICATION/DESCRIPTION

* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

- BODY MATERIAL : ALUMINUM
- INPUT VOLTAGE : 180-260 VAC
- LED CHIP : CREE
- POWER : 7W
- LUMINOUS FLUX : 800lm
- EFFICACY : >80lm/W
- COLOR RENDERING INDEX : >80
- LED COLOR TEMPERATURE : 2700-5000K
- VIEW ANGLE : 15°/24°/38°
- THDi : 15%
- POWER FACTOR : >0.95
- WORKING TEMPERATURE : -10-50°C
- LIGHTING SOURCE LIFE : 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	D	H	
XZ-TL-67W-081	7	SMD	90	75	



LED DOWNLIGHT TL-10W-081

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY
AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 10W
LUMINOUS FLUX	: 850lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	D	H	
XZ-TL-10W-081	10	SMD	144	90	



LED DOWNLIGHT TL-12W-081

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 12W
LUMINOUS FLUX	: 1100lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	D	H	
XZ-TL-12W-081	12	SMD	144	90	



LED DOWNLIGHT TL-20W-081

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 20W
LUMINOUS FLUX	: 1700lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	D	H	
XZ-TL-20W-081	20	SMD	138	120	



LED DOWNLIGHT TL-25W-081

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY
AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 25W
LUMINOUS FLUX	: 2200lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	D	H	
XZ-TL-25W-081	25	SMD	138	120	



LED DOWNLIGHT TL-30W-081

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 30W
LUMINOUS FLUX	: 2600lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	D	H	
XZ-TL-30W-081	30	SMD	138	120	



LED DOWNLIGHT TL-35W-081

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 35W
LUMINOUS FLUX	: 3000lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 15°/24°/38°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	D	H	
XZ-TL-35W-081	35	SMD	165	145	



LED DOWNLIGHT TL-50W-081

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: CREE
POWER	: 50W
LUMINOUS FLUX	: 4200lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-5000K
VIEW ANGLE	: 24°/60°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	D	H	
XZ-TL-50W-081	50	SMD	190	155	