



## DCH RADIO REMOTE CONTROL

DCH รีโมทควบคุมระยะไกลสำหรับรถและ เครื่องไฟฟ้าพร้อม  
ความปลอดภัยที่สูงขึ้นด้วยปุ่มหยุดฉุกเฉินขนาดใหญ่บริเวณ  
ด้านบนของตัวรีโมท รีโมท DCH มียาวซีลโดยรอบของรีโมท  
ป้องกันระดับ IP65 ได้รับรองมาตรฐานการผลิต CE และ FCC



# DCH



## PRODUCT INFORMATION



| Model                   | Functions   |
|-------------------------|---|
| DCH-A21                 | (4) single speed pushbuttons + (2) AUX single speed pushbuttons + (1) Start + (1) Horn/light  |
| DCH-A21(A+B)            | (4) single speed pushbuttons + (2) AUX single speed pushbuttons + (1) Start + (1) I/II Select |
| DCH-A22                 | (4) double speed pushbuttons + (2) AUX single speed pushbuttons + (1) Start + (1) Horn/light  |
| DCH-A22(A+B)            | (4) double speed pushbuttons + (2) AUX single speed pushbuttons + (1) Start + (1) I/II Select |
| DCH-A31                 | (6) single speed pushbuttons + (1) Start + (1) Horn/light                                     |
| DCH-A31(A+B)            | (6) single speed pushbuttons + (1) Start + (1) I/II Select                                    |
| DCH-A32                 | (6) double speed pushbuttons + (1) Start + (1) Horn/light                                     |
| DCH-A32(A+B)            | (6) double speed pushbuttons + (1) Start + (1) I/II Select                                    |
| DCH-A41                 | (8) single speed pushbuttons + (1) Start + (1) Horn/light                                     |
| DCH-A41(A+B)            | (8) single speed pushbuttons + (1) Start + (1) I/II Select                                    |
| DCH-A42                 | (8) double speed pushbuttons + (1) Start + (1) Horn/light                                     |
| DCH-A42(A+B)            | (8) double speed pushbuttons + (1) Start + (1) I/II Select                                    |
| Radio Remote Control    | Specification   |
| Certificate             | ISO 9001:2015   |
| Protection              | IP 65   |
| Distance                | >150M   |
| Temperature             | -25 °C - 70°C   |
| Button life             | >2,000,000 times  |
| Continuous Working Time | 400 hours (at room temperature)   |



E-catalog