

APPLICATION INDUSTRY CASES



工程机械行业应用 Construction Machinery Industry Application



TITAN[®]

SERVICE

TITAN SERVICE CO., LTD.

SMALL JOYSTICK S SERIES

1. Panel can be made according to customer requirements.





2. Germany Gessmann joystick.



3. Japan IDEC Emergency Stop.



4. 4 pieces side buttons convenient use.



5. DCH iKey can make sure all same models working normally after you change the DCH iKey.

TECHNICAL PARAMETERS OF JOYSTICK S SERIES

Type	S00	S32	S34	S42	S44
Transmitter Function	Max 20 I/O output	1 single shaft two-speed joystick +1cross shaft two-speed joystick +10 I/O	1 single shaft four-speed joystick +1cross shaft four-speed joystick +10 I/O	2 cross shaft two-speed joystick +10 I/O	2 cross shaft four-speed joystick +10 I/O
Transmitter Dimensions	293×146×183mm				
Transmitter Weight	1300g	1500g			
Transmitter Antenna	Inside				
Receiver Antenna	Outside				
Start	Short press + long press start button				
Emergency	Mushroom conforms to EN3849-1 standard				
Housing	Plastics				
IP class	IP65				
Intelligent Key	DCH iKey				
Distance	≥100 meters				
Temperature	-25℃~+70℃				
Frequency	433-434MHZ				
Button life	≥2,000,000times				
Power supply	2500mA Li-ion battery				
Continuous working time	50 hours (at room temperature)				
Automatic shutdown	15 minutes,30 minutes or no shutdown				
Button Text	Arrow/English/Chinese/Others				
Receiver Output	Relay/Canopen/DP/PWM/DeviceNet/RS485/Modbus/SAE J1939				
Receiver Voltage	30-280VAC,57-528VAC,18-36VDC				

DCH



CE FC