

AXIS M2025-LE Network Camera

Affordable and outdoor-ready camera with built-in IR

AXIS M2025-LE is a small, bullet-style camera delivering high-quality images in HDTV resolution. It has built-in IR illumination that enables surveillance up to 15 m even at nighttime. The outdoor-ready camera is resistant to rough weather and the integrated sunshield protects against sun and rain. With a 115° field of view, a single camera gives full surveillance at low cost, and Axis' Corridor Format provides efficient monitoring of corridors and shopping aisles. WDR – Forensic Capture increases forensic usability by highlighting details in both dark and well-lit areas. The spacious back box enables secure cable management and easy installation.

> **Outdoor-ready, IP66- and NEMA 4X-rated**

> **HDTV 1080p**

> **Built-in IR illumination**

> **115° field of view**

> **Zipstream**



AXIS M2025-LE Network Camera

Models	AXIS M2025-LE AXIS M2025-LE Black	Casing	IP66-, NEMA 250 Type 4X-, and IK08-rated, polymer casing Encapsulated electronics, Captive screws (Torx 10) M2025-LE: Color: White NCS S 1002-B M2025-LE Black: Color: Black NCS S 9000-N
Camera		Sustainability	PVC free
Image sensor	1/2.8" progressive scan RGB CMOS	Memory	512 MB RAM, 256 MB Flash
Lens	M12 mount, Fixed iris, Fixed focus 2.8 mm, F2.0 Horizontal field of view: 115° Vertical field of view: 64°	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2 Typical: 4.1 W, Max.: 6.3 W
Day and night	Automatically removable infrared-cut filter	Connectors	RJ45 10BASE-T/100BASE-TX PoE
Minimum illumination	Color: 0.2 lux at 50 IRE, F2.0 B/W: 0.04 lux at 50 IRE, F2.0 0 lux with IR illumination on	IR illumination	Power-efficient, long-life 850 nm IR LED. Range of reach up to 15 m (50 ft) depending on scene
Shutter time	1/65000 s to 2 s	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Video		Operating conditions	-30°C to 50°C (-22 °F to 122 °F) Humidity 10–100% RH (condensing)
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Resolutions	1920x1080 to 160x90	Approvals	EMC EN 55032 Class A, EN 55024, IEC 62471, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-78, IEC 60068-2-14, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 62262 IK08, IEC/EN 60529 IP66, NEMA 250 Type 4X Safety IEC/EN/UL 60950-22
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz	Dimensions	Height, straight: 174 mm (6.9 in) Height, angled: 118 mm (4.6 in) ø 101 mm (4.0 in)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth Axis' Zipstream technology in H.264 VBR/MBR H.264	Weight	0.5 kg (1.1 lb)
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate streaming	Included accessories	Installation Guide, Windows decoder 1-user license, Torx L-key, Connector guard
Image settings	Compression, Color, Brightness, Sharpness, Contrast, Local contrast, White balance, Exposure control, WDR – Forensic Capture: up to 115 dB depending on scene. Rotation: 0°, 90°, 180°, 270° including Corridor Format, Text and image overlay, Privacy masks, Mirroring of images	Optional accessories	AXIS T94B03L Recessed Mount AXIS T94B02D Pendant kit AXIS T94B01P Conduit Back Box AXIS T94B02M J-Box/Gang Box Plate Axis mounts AXIS Surveillance microSDXC™ Card For more accessories, see www.axis.com AXIS T94 mounts for various installations AXIS Surveillance microSDXC™ Card
Pan/Tilt/Zoom	Digital PTZ	Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Network		Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i>	
System integration		Environmental responsibility: www.axis.com/environmental-responsibility	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org		
Analytics	AXIS Video Motion Detection 3, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap		
Event triggers	Analytics, Edge storage events		
Event actions	Notification: email, HTTP, HTTPS and TCP and SNMP trap Video recording to edge storage Send video clip Pre- and post-alarm video buffering Overlay text		
Data streaming	Event data		
Built-in installation aids	Pixel counter		
General			