Specifications



Enclosure, EVlink Pro AC Metal, IP66, pedestal mount in metallic kit enclosure, for 25mm<sup>2</sup> to 35mm<sup>2</sup> cable

EVA1RFKES

### Main

Mann		
Range	EVlink	
product name	EVlink Pro AC Metal	
Product or component type	Enclosure	
Range compatibility	EVlink EVlink Pro AC EVB3 charging station	
Poles description	3P + N	
Mounting mode	Assembled	
Localisation on device	On lower part	
rated supply voltage	380415 V CA 50/60 Hz 220240 V CA 50/60 Hz	
Earthing system	TT TN-S TN-C-S IT Compatible IT with additional isolation transformer on the power supply	

## Complementary

Provided equipment	1 mounting plate 2 DIN rail 4 fixing bracket 3 cable gland	
DIN rail length	240 mm	
Mounting plate description	Telequick perforated	
Cable entry number	2 cable gland for M32 1 cable gland for M12	
Cable cross section	2535 mm <sup>2</sup>	
Height	360 mm	
Width	270 mm	
Depth	180 mm	
Net weight	3.4 kg	

## Environment

IP degree of protection	IP66
IK degree of protection	IK09
Ambient air temperature for operation	-3070 °C

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.000 cm
Package 1 Width	29.000 cm
Package 1 Length	38.000 cm
Package 1 Weight	3.266 kg
Unit Type of Package 2	P12
Number of Units in Package 2	40
Package 2 Height	109.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	154.000 kg

# Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability  $\geq$ 

#### **Use Better**

Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
SCIP Number	A18cb304-12b9-4d34-8ea6-7f2f757726a8