

Charging station, Schneider Charge, 1P+N, attached cable 5m, 7.4kW, 32A

EVH5A07N2C5

Main

Range	Schneider Charge	
Product name	Schneider Charge	
Product or component type	Charging station	
Poles description	1P + N	
Mounting mode	Wall-mounted	
Max power	7.4 kW 32 A	
Number of charge point	1	
Connection to the vehicle	Attached cable T2 bottom 5 m	

Complementary

rated supply voltage	230240 V AC 5060 Hz +/- 10 %	
Earthing system	IT 230 TT TN-S	
Number of inputs	1	
Input type	Dry contact for dynamic energy management	
Local signalling	Red, green and blue 1 LED, function: status indication	
Protection type	Earth-leakage protection	
Height	352 mm	
Width	244 mm	
Depth	117 mm	
Net weight	4.5 kg	
Colour	White/green	
Standards	EN 61851 IEC 61851-1	
Communication network type	Wi-Fi Wireless Ethernet	
Communication port protocol	OCPP 1.6, for connection to the Schneider Electric Wiser app	

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529	
IK degree of protection	IK10	
Ambient air temperature for operation	-3050 °C	

Ambient air temperature for storage	-4085 °C
Relative humidity	595 %
Operating altitude	02000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.500 cm
Package 1 Width	29.000 cm
Package 1 Length	48.000 cm
Package 1 Weight	6.710 kg
Unit Type of Package 2	P12
Number of Units in Package 2	18
Package 2 Height	102.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	132.000 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	645
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	Ab6451be-b3f4-4070-b9b6-e8f0e546f1eb
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information

EVH5A07N2C5

Offer Marketing Illustration

Product benefits / Features

