

Charging cable, EVlink, 10m, 32A, 1-Phase, T2 connector at each end of cable

EVP1CNX32122

Main

Range	EVlink
Product or component type	Charging cable
Accessory / separate part category	Cabling accessory
Network number of phases	Single phase
Poles description	1P + N
[In] rated current	32 A
[Us] rated supply voltage	220240 V AC 50/60 Hz
Socket number	2

Complementary

plug type	T2 / silver plated contacts charging station end	
Connector type	T2 vehicle end silver plated contacts T2 charging station end silver plated contacts	
Range compatibility	EVlink EVlink parking EVF1 charging station EVlink EVlink parking EVW1 charging station EVlink EVlink parking EVF2 charging station EVlink EVlink parking EVW2 charging station EVlink EVlink Smart Wallbox EVB1 charging station EVlink EVlink Wallbox EVH2 charging station EVlink EVlink Pro AC EVB3 charging station EVlink EVlink Pro AC Metal EVB3 charging station	
Standards	IEC 62196-2 IEC 62196-1	
Product certifications	CE	
Length	10 m	
Net weight	4.5 kg	
Colour	Grey	

Environment

IP degree of protection	IP44 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Ambient air temperature for operation	-3050 °C	
Ambient air temperature for storage	-4080 °C	
Relative humidity	595 %	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	35.000 cm
Package 1 Length	50.000 cm
Package 1 Weight	3.662 kg
Unit Type of Package 2	S06
Number of Units in Package 2	25
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	100.600 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

⊗ Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
SCIP Number	0a787687-ca4b-4982-8684-548a3b52ac76
REACh Regulation	REACh Declaration