## 10K CAST STAINLESS STEEL BALL VALVE FLANGED ENDS

KITZ Fig: 10UTDZM Sizes: 1/2-8inch(15-200mm)

ANTI-STATIC DEVICE, FULL BORE, CONFORM TO ISO5211

Standards

. End to End: ASME B16.10 CLASS 150 . End Connection: JIS B2220 10K

. Wall Thickness: ASME B16.34 CLASS 150

Test Standard
. KITZ STANDARD

Approvals

Japan Valve Manufacturer's Association 15-200 mm (1/2-8 inch)

approved Dimensions

n/mm)	L	L1	Н	D1	Kg
15	108.0	0.0	108.0	130.0	0.00
20	117.0	0.0	111.0	130.0	0.00
25	127.0	0.0	124.0	160.0	0.00
32	140.0	0.0	128.0	160.0	0.00
40	165.0	0.0	134.0	230.0	0.00
50	178.0	0.0	143.0	230.0	0.00
65	190.0	0.0	179.0	400.0	0.00
80	203.0	0.0	188.0	400.0	0.00
100	229.0	0.0	224.0	460.0	0.00
125	356.0	0.0	240.0	460.0	0.00
150	394.0	0.0	314.0	1000.0	0.00
200	457.0	0.0	406.0	1500.0	0.00
	15 20 25 32 40 50 65 80 100 125 150	15 108.0 20 117.0 25 127.0 32 140.0 40 165.0 50 178.0 65 190.0 80 203.0 100 229.0 125 356.0 150 394.0	15     108.0     0.0       20     117.0     0.0       25     127.0     0.0       32     140.0     0.0       40     165.0     0.0       50     178.0     0.0       65     190.0     0.0       80     203.0     0.0       100     229.0     0.0       125     356.0     0.0       150     394.0     0.0	15     108.0     0.0     108.0       20     117.0     0.0     111.0       25     127.0     0.0     124.0       32     140.0     0.0     128.0       40     165.0     0.0     134.0       50     178.0     0.0     143.0       65     190.0     0.0     179.0       80     203.0     0.0     188.0       100     229.0     0.0     224.0       125     356.0     0.0     240.0       150     394.0     0.0     314.0	15       108.0       0.0       108.0       130.0         20       117.0       0.0       111.0       130.0         25       127.0       0.0       124.0       160.0         32       140.0       0.0       128.0       160.0         40       165.0       0.0       134.0       230.0         50       178.0       0.0       143.0       230.0         65       190.0       0.0       179.0       400.0         80       203.0       0.0       188.0       400.0         100       229.0       0.0       224.0       460.0         125       356.0       0.0       240.0       460.0         150       394.0       0.0       314.0       1000.0




NAME OF DARK	HATERIAL	CDECTETCATION
NAME OF PART	MATERIAL	SPECIFICATION
BODY	STAINLESS STEEL	A351 Gr.CF8M/SCS14A
BODY CAP	STAINLESS STEEL	A351 Gr.CF8M/SCS14A
STEM	STAINLESS STEEL	316SS
BALL	STAINLESS STEEL	A351 Gr.CF8M/SCS14A

**Specifications** 

10K CAST STAINLESS STEEL BALL VALVE FLANGED ENDS, ANTI-STATIC DEVICE, FULL BORE, CONFORM TO ISO5211

End to End: ASME B16.10 CLASS 150, End Connection: JIS B2220 10K, Wall Tchickness: ASME B16.34 CLASS 150, Test Standard: KITZ STANDARD, Sizes: 1/2-8inch(15-200mm), Approvals: Japan Valve Manufacturer's Association 15-200 mm (1/2-8 inch), BODYMATERIAL: STAINLESS STEEL, BODY CAPMATERIAL: STAINLESS STEEL, BALLMATERIAL: STAINLESS STEEL, KITZ Fig: 10UTDZM





Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



