CLASS 125 CAST IRON Y TYPE STRAINER FLANGED ENDS

KITZ Fig: 125FCY

Sizes: 2-14inch(50-350mm)

BOLTED COVER, FLAT FACE FLANGED ENDS.

Standards

. End to End: KITZ STANDARD

. End Connection: ASME B16.1 CLASS 125

. Wall Thickness: KITZ STANDARD

Test Standard . KITZ STANDARD

Dimensions

SIZE(inch/mm)		L	L1	Н	D1	Kg
2	50	250.0	0.0	157.0	0.0	0.00
21/2	65	285.0	0.0	207.0	0.0	0.00
3	80	315.0	0.0	237.0	0.0	0.00
4	100	370.0	0.0	278.0	0.0	0.00
5	125	420.0	0.0	321.0	0.0	0.00
6	150	490.0	0.0	367.0	0.0	0.00
8	200	570.0	0.0	457.0	0.0	0.00
10	250	680.0	0.0	536.0	0.0	0.00
12	300	800.0	0.0	625.0	0.0	0.00
14	350	950.0	0.0	741.0	0.0	0.00

Material List

NAME OF PART	MATERIAL	SPECIFICATION
BODY	CAST IRON	FC200
COVER	CAST IRON	FC200

Specifications


CLASS 125 CAST IRON Y TYPE STRAINER FLANGED ENDS, BOLTED COVER,

FLAT FACE FLANGED ENDS.

End to End: KITZ STANDARD, End Connection: ASME B16.1 CLASS 125, Wall Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes: 2-14inch(50-350mm), BODYMATERIAL: CAST

IRON, COVERMATERIAL : CAST IRON, KITZ Fig : 125FCY





For more details, please refer to the drawing.

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



