CLASS 150 CAST STAINLESS STEEL GATE VALVE FLANGED ENDS

KITZ Fig: 150UMAT

Sizes: 1/2-8inch(15-200mm)

BOLTED BONNET, OUTSIDE SCREW & YOKE.

Standards

End to End: ASME B16.10 CLASS 150
End Connection: ASME B16.5 CLASS 150
Wall Thickness: ASME B16.34 CLASS 150

Test Standard . API 598

Dimensions

SIZE(inch/mm)		L	L1	Н	D1	Kg
1/2	15	108.0	0.0	201.0	90.0	0.00
3/4	20	117.0	0.0	210.0	90.0	0.00
1	25	127.0	0.0	224.0	100.0	0.00
11/2	40	165.0	0.0	284.0	140.0	0.00
2	50	178.0	0.0	336.0	160.0	0.00
21/2	65	190.0	0.0	374.0	180.0	0.00
3	80	203.0	0.0	444.0	200.0	0.00
4	100	229.0	0.0	523.0	225.0	0.00
5	125	254.0	0.0	606.0	250.0	0.00
6	150	267.0	0.0	711.0	250.0	0.00
8	200	292.0	0.0	924.0	300.0	0.00

Material List

matoriat Erot						
NAME OF PART	MATERIAL	SPECIFICATION				
BODY	STAINLESS STEEL	A351 Gr.CF8/SCS13A				
BONNET	STAINLESS STEEL	A351 Gr.CF8/SCS13A				
STEM	STAINLESS STEEL	304SS				
DISC	STAINLESS STEEL	A351 Gr.CF8/SCS13A				



CLASS 150 CAST STAINLESS STEEL GATE VALVE FLANGED ENDS, BOLTED BONNET, OUTSIDE SCREW & YOKE.

End to End: ASME B16.10 CLASS 150, End Connection: ASME B16.5 CLASS 150, Wall Tchickness: ASME B16.34 CLASS 150, Test Standard: API 598, Sizes: 1/2-8inch(15-200mm), BODYMATERIAL: STAINLESS STEEL, BONNETMATERIAL: STAINLESS

STEEL, DISCMATERIAL : STAINLESS STEEL, KITZ Fig : 150UMAT









