CLASS 150 CAST BRONZE GATE VALVE SCREWED ENDS

KITZ Fig: AK150LU Sizes: 1/4-2inch(8-50mm) UNION BONNET, INSIDE SCREW

Standards

End to End: KITZ STANDARDEnd Connection: ASME B1.20.1Wall Thickness: KITZ STANDARD

Test Standard
. KITZ STANDARD

Dimensions

D I MOTIO I OTTO						
SIZE(inch/mm)		L	L1	Н	D1	Kg
1/4	8	45.0	0.0	122.0	50.0	0.00
3/8	10	46.0	0.0	122.0	50.0	0.00
1/2	15	51.0	0.0	144.0	55.0	0.00
3/4	20	56.0	0.0	164.0	70.0	0.00
1	25	66.0	0.0	185.0	70.0	0.00
11/4	32	68.0	0.0	219.0	80.0	0.00
11/2	40	74.0	0.0	258.0	90.0	0.00
2	50	84.0	0.0	303.0	100.0	0.00

Material List


NAME OF PART	MATERIAL	SPECIFICATION	
BODY	CAST BRONZE	B62	
BONNET	CAST BRONZE	B62	
STEM	BRONZE	B62	
DISC	CAST BRONZE	B62	

Specifications

CLASS 150 CAST BRONZE GATE VALVE SCREWED ENDS, UNION BONNET, INSIDE SCREW

End to End: KITZ STANDARD, End Connection: ASME B1.20.1, Wall Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes: 1/4-2inch(8-50mm), BODYMATERIAL: CAST BRONZE, BONNETMATERIAL: CAST BRONZE, STEMMATERIAL: BRONZE, DISCMATERIAL: CAST BRONZE, KITZ Fig: AK150LU





For more details, please refer to the drawing.

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



