CLASS 150 CAST BRONZE GLOBE VALVE SCREWED ENDS

KITZ Fig: C

Sizes: 1/4-3inch(8-80mm) SCREWED BONNT, INSIDE SCREW.

Standards

End to End: KITZ STANDARDEnd Connection: JIS B0203Wall Thickness: KITZ STANDARD

Test Standard . KITZ STANDARD

Dimensions

SIZE(inch/	nm)	L	L1	Н	D1	Kg
1/4	8	44.0	0.0	64.0	50.0	0.00
3/8	10	44.0	0.0	66.0	50.0	0.00
1/2	15	53.0	0.0	77.0	60.0	0.00
3/4	20	65.0	0.0	92.0	70.0	0.00
1	25	77.0	0.0	103.0	80.0	0.00
11/4	32	85.0	0.0	125.0	90.0	0.00
11/2	40	100.0	0.0	144.0	100.0	0.00
2	50	119.0	0.0	173.0	115.0	0.00
21/2	65	139.0	0.0	198.0	135.0	0.00
3	80	158.0	0.0	213.0	155.0	0.00



mator rat 210t						
NAME OF PART	MATERIAL	SPECIFICATION				
BODY	CAST BRONZE	CAC				
BONNET	FORGED BRASS	CAC				
STEM	BRASS	C3531				
DISC	CAST BRONZE	CAC406C				




CLASS 150 CAST BRONZE GLOBE VALVE SCREWED ENDS, SCREWED

BONNT, INSIDE SCREW.

End to End : KITZ STANDARD, End Connection : JIS B0203, Wall

Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes: 1/4-3inch(8-80mm), BODYMATERIAL: CAST BRONZE, BONNETMATERIAL: FORGED BRASS, STEMMATERIAL: BRASS, DISCMATERIAL: CAST BRONZE, KITZ Fig: C





Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



