10K CAST BRONZE BALL VALVES, WITH ELECTRIC ACTUATOR KELMO

KITZ Fig: ED24-TE Sizes: 3/8-2inch(10-50mm) REDUCED BORE, SCREWED ENDS.

Standards

End to End: KITZ STANDARDEnd Connection: JIS B0203 (7)Wall Thickness: KITZ STANDARD

Test Standard
. KITZ STANDARD

Dimensions

211101101010						
SIZE(inch/mm)		L	L1	Н	D1	Kg
3/8	10	46.0	22.0	112.0	0.0	0.00
1/2	15	65.0	32.5	117.5	0.0	0.00
3/4	20	68.0	34.0	121.5	0.0	0.00
1	25	79.0	39.5	120.5	0.0	0.00
11/4	32	86.0	43.0	124.5	0.0	0.00
11/2	40	96.0	48.0	138.5	0.0	0.00
2	50	109.0	54.5	144.5	0.0	0.00

Material List

NAME OF PART	MATERIAL	SPECIFICATION	
ВОДУ	CAST BRONZE	CAC406	
BODY CAP	FORGED BRASS	C3771	
STEM	HIGH TENSION BRASS	C6782(5)	
BALL	BRASS(2)(4)	C3531	




10K CAST BRONZE BALL VALVES, WITH ELECTRIC ACTUATOR KELMO, REDUCED BORE, SCREWED ENDS.

End to End: KITZ STANDARD, End Connection: JIS B0203 (7), Wall Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes: 3/8-2inch(10-50mm), B0DYMATERIAL: CAST BRONZE, B0DY CAPMATERIAL: FORGED BRASS, STEMMATERIAL: HIGH TENSION BRASS, BALLMATERIAL

:BRASS(2)(4), KITZ Fig : ED24-TE





- For more details, please refer to the drawing.

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



