

Back Up Rings

Profile	Type	Standard material	Pressure (bar)	Temperature (°C)	Surface speed (m/sec)
	BUR08	PU POM PTFE	-	-30 to 105 -60 to 100 -200 to 260	-
	BUR09	PU POM PTFE	-	-30 to 105 -60 to 100 -200 to 260	-
	BUR10	PU POM PTFE	-	-30 to 105 -60 to 100 -200 to 260	-
	BUR11	PU POM PTFE	-	-30 to 105 -60 to 100 -200 to 260	-
	BUR12	PU POM PTFE	-	-30 to 105 -60 to 100 -200 to 260	-
	BUR13	PU POM PTFE	-	-30 to 105 -60 to 100 -200 to 260	-
	BUR05	PU POM PTFE	-	-30 to 105 -60 to 100 -200 to 260	-

หมายเหตุ : ค่าที่กำกับนี้เป็นคุณสมบัติสูงสุดของวัสดุในแต่ละชนิด แนะนำให้เผื่อค่าไว้บ้างในการใช้งานจริง
 NOTE : These indicated specifications are presented the maximum values of each material



บริษัท เทอร์มินอลซีล แอนด์ เซอร์วิส จำกัด
 TERMINALSEAL AND SERVICE CO.,LTD.



บริษัท เทอร์มินอล แมชชีนเวิร์ค จำกัด
 TERMINAL MACHINERWORK CO.,LTD.



บริษัท ที.เอ็ม.จี. รันเบอร์พาร์ท จำกัด
 T.M.G. RUBBERPART CO.,LTD.

Tel : +66 (0) 2942-9979 (Auto)
Fax : +66 (0) 2942-9980 (Auto)
Email: terminalseal@terminalseal.com