



BG69

	Chip	Ingenic T31 ZL
	Sensor	GC2063
	Pixel	2MP
	Features	<ol style="list-style-type: none"> 1. Exclusive private model, 2MP, 2.5 inch; 2. PIR + Radar dual induction alarm recording, Within 1 second recording; 3. Low power + Solar charging, Never power off 4. Standard 10000MA, can be customized 20000MA battery power supply, and Low-battery alert; 5. Waterproof & dustproof, Two-way talk; 6. Cloud Storage, TF card storage, Max supports 256G; 7. Humanoid detection and alarm pushing; 8. Full color night vision 9. Free Cloud Storage recording
Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/Image sensor	1/2.9 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0.1 Lux(B&W mode)
	Lens/Viewing angle	4mm@F2.0/107°Diagonal
	Night vision	IR-CUT with auto-switching, 6PCS IR LED lights; Irradiation distance: 10~15 m
	Compression standard	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Data Rate	Main stream: 1080p(1920×1080)@15fps/1296p(2304×1296)@15fps Substream: 360p(640×360)@15fps
	Bit rate/maximum frame rate	128~4096kbps/30fps

Shenzhen VStarcam Technology Co., Ltd

	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in —38dB microphone
	Output	Built-in 8Ω2 W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/64kbps
Network	4G(Chinese version) LTE	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8
	4G(European version) LTE	WCDMA: B1/B5/B8 FDD: B1/B3/B5/B7/B8/B20 TDD:B38/B40/B41
Pan & Tilt	Pan & Tilt	Pan 345° /Tilt 55°
	Preset position	Supports 16 (Mobile phone App supports 5) preset positions
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage
Alarm	Alarm detection	Radar detection; Humanoid detection
Physical Indicators	Rated voltage	DC5V±5%
	Power supply	Supports four 18650 and four 21700 batteries
	Power consumption	Rated power: 5W (with IR LED lights ON)/Max power: 11W (with Pan & Tilt ON)
	Operating condition	Temperature: -10~50°C; Humidity: <90%
	Weight	(Note: in kind prevail)