

Specifications Model: C24S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	CPU/Image sensor	1/2.7 inch 1080p Progressive Scan CMOS
	Minimum illumination	0.5Lux (Color mode) ,0Lux (B&W Mode)
	Lens/Viewing Angle	4.0mm@F2.0/84° (diagonal)
	Night vision	Dual Filter,IR-Cut, 6pcs 850nm patch IR LED; IR irradiation distance:5~10m
Video	Encode format	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Resolution	Main Stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@30fps Substream: 360p(640×360)@15fps
	Bit Rate/Maximum frame rate	128~4096kbps/30fps
	Image adjustment	Brightness and contrast can be adjusted
Audio	Input	Built-in -38 dB microphone
	Output	Built-in speaker(8Ω1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n; Supports AP mode
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan-tilt	Pan-tilt	Pan: 345°,Tilt: 84°
	Preset position	Supports 16(Mobile phone App supports 5) preset positions
Memory	Memory function	Supports T-Flash card; Maximum support 256GB; Cloud storage; NVR; NAS
Alarm	Alarm Trigger	Motion detection; Humanoid detection; Humanoid tracking; Crying detection; Smoke alarm detection; Absence detection
Physical Environmental	Rated voltage	DC 5V±5%
	Power consumption	Related power:2.5W(With IR LED on), Maximum Power: 5.6W (With Pan&Tilt on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Net: 245g Gross: 520g (Note: in kind prevail)
	Package size	197*157*120 mm(L×W×H)