

**HP-30MPT30W**



# MINI PT CAMERA

3MPixel Wireless Connection LED Light



**P6slite**



**3M PIXEL HD**  
WIFI Camera Series

# MINI PT CAMERA

3MPixel Wireless Connection LED Light



## Feature

- Resolution 1/3" CMOS Sensor (3MP)
- Effective Pixels 2048\*1536
- Focus Length Board Lens 3.6mm/F1.3
- Infrared LED 4PCS Warmlight and 4pcs IR LED Meter: 25M
- Infrared Distance 25M
- Audio Two way Audio
- SD Card Support MAX 128G
- Support Built-in WIFI
- Power Source DC12V±10%, 500mA

## Specification

Model	HP-30MPT30W
Image Sensor	1/3" High-resolution CMOS Sensor
Resolution	3MP
Effective Pixels	2048*1536
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥39dB
Scanning System	Progressive
Video Output	RJ45, WIFI
Reset Button	YES
<b>PTZ</b>	
Horizontal Rotation	Range 0~355
Tilt Rotation Range	0~90
Speed	30 / SEC.
<b>LENS Type</b>	
Focus Length	Board Lens 3.6mm / F1.3
Focus Control	Fixed
Lens Type	Fixed
Pixels	3MP
<b>Night Vision</b>	
Infrared LED	4PCS Warmlight and 4pcs IR LED Meter: 25M
Infrared Distance	25M
IR Status	Under 5 Lux By Auto
IR Power	On CDS Auto Control
<b>Camera</b>	
Day/Night	Default night vision is black and white , when there are objects moving, the video will be converted to color;
Image Config	Saturation / Brightness / Contrast / Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control)
Corridor Pattern	Support
OSD	Support WEB and APP Control
BLC / WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR / NAS / VMS / Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands, Czech
<b>Interface</b>	
Audio	Two way Audio
Alarm	Support humanoid automatic tracking, two way Audio,Built-in loudspeaker warning,Speaker alarm can record its own sound;
SD Card Slot	Support MAX 128G
Wifi	Support Built-in WIFI
<b>General</b>	
Housing	Plastic IP66
Anti-cut Bracket	Anti-Cut 3-Axis
IR Cut Filter	YES
Operation Temperature	-20 ~ +60 RH95% Max
Storage Temperature	-20 ~ +60 RH95% Max
Power Source	DC12V ± 10%, 500mA
Dimension	Size: 130x130)x 87mm
Weight	Weight 0.5g



**P6slite**

