



5000 SERIES

IP CAMERA SUVEILANCE

HP-55B40PE-M



4M PIXEL HD

IP Camera Series

4M
PIXEL

H.265X
H.264
Compression

DAY &
Night
Support

LED
SMART

D-WDR
Support

PoE
Support

Audio
Support

ONVIF
Support



5000 SERIES

IP CAMERA SURVEILLANCE



Feature

- 4.0 Megapixel
- 1/2.8" progressive scan CMOS
- H.265+ (Compatible with H.265/H.264)
- Color: 0.01Lux @ (F1.6, AGC ON)
B/W: 0.001 Lux @ (F1.6, AGC ON)
- 3.6mm @ F1.6 Fixed Iris lens
- IR Type6 x IR Array Dual Light
- IR Distance 20 - 30m
- Audio In/out 1 x Built in MIC
- Hiview DDNS Supported
- ONVIF Support
- Power 12V DC / PoE (IEEE802.3af)
- Protection Level IP66

Specification

Model	HP-55B40PEL-M
Image Sensor	1/2.8" progressive scan CMOS
Pixels	4.0 Megapixel
Min. Illumination	Color: 0.01Lux @ (F1.6, AGC ON) B/W: 0.001 Lux @ (F1.6, AGC ON)
Shutter Speed	1/50(1/60) - 1/10,000s
Shutter Mode	Weak / In / Strong
Day / Night	Auto (ICR) / Color / B/W
Wide Dynamic Range	DWDR
White Balance	Auto
Gain Control	Auto
Backlight Compensation	BLC / ATW / AGC / DWDR
Signal System	PAL / NTSC
Anti Flicker	Supported
Image Control	Brightness / contrast / Saturation / Hue
Lens	
Mount Type	Φ12
Auto Iris	Auto Electric Iris
Focal Length	3.6mm @ F1.6 Fixed Iris lens
Focus Control	Fixed
Angle of View	82°
Infrared	
IR Type	6 x IR Array Dual Light
IR Distance	20 - 30m
IR Intensity	Smart IR
Light Mode	Intelligent variable light / Smart alert Smart infrared
Video	
Compression	H.265 +(Compatible with H.265/H.264)
Image Resolution	Main stream: 4MP /3MP / 2MP / 720MP Secondary stream: D1 /HD1 / CIF / AVGA
Frame Rate	Main stream: 4MP@20fps Secondary stream: D1@20fps
Bitrate	1024kbps - 8Mbps
Bitrate Control	VBR / CBR
Multi-stream	Dual steam
Caption	Date and time / Alarm / Customized
Digital Noise Reduction	3D noise reduction
Digital Defog	Supported

