



**3MP** PIXEL **HD**  
4G PT Dome camera



## Feature **3MP** **HD**

- \* 4G PT Dome camera 4G
- \* Resolution 3MP
- \* Sensor 1/3" CMOS Sensor
- \* Shutter Shutter adaptation
- \* Lens 4mm
- \* IR Distance IR 20-30m, spotlight 15m
- \* Video Compression H.265 / H.264
- \* Frame Rate Max 15fps
- \* Interface Micro SD Card (max 256G)
- \* Cloud Storage Support
- \* Power Adapter DC 12V 1A

## Specification

Model	HW-33MPT302-4G
Resolution	3MP
Sensor	1/3" CMOS Sensor
Shutter	Shutter adaptation
Lens	4mm
Rotation Angle	Pan: 0-263 0.1-20/S Tilt :0-105 0.1-20/S
Day-night	mode Infrared filter
DNR	3D digital noise reduction
Dynamic Range	Digital WDR
IR Distance	IR 20-30m, spotlight 15m (depends on environment)
<b>Compression Standard</b>	
Video Compression	H.265 / H.264
Video Compression	HD / SD
Audio Coding Format	AAC / G711A
<b>Image</b>	
Resolution	Main stream: 2304 *1296 Sub stream: 640x360
Frame Rate	Max 15fps
Image reversal	Support mirror and flip reversal
Privacy Masking	Support
<b>Alarm Function</b>	
Intelligent Alarm	Motion detection
Alarm Notification	Alarm notification push
<b>Storage</b>	
Interface	Micro SD Card (max 256G)
Cloud Storage	Support
<b>Wireless Spec:</b>	
Wireless Standard	4G: LTE-TDD/LTE FDD; WIFI:802.11bgn
Wireless Frequency Band	LTE-FDD: B1/B3/B5/B8 LTE-TDD: B40 WIFI: 2400MHz-2483.5MHz
<b>General Specs:</b>	
Working Temperature	-20C-50C, Working Humidity: <95%
Working Humidity	<95% <95% (no condensation)
Power Adapter	DC 12V 1A