

# AJB-IPC409S2-03(SU6)

## Main Feature

- Plastic IR Dome Camera
- HD CMOS Sensor: 1/2.8" 2.0MP SONY322 D-WDR
- POE/WIFI/Audio (Optional)
- ONVIF 2.4, P2P
- iPhone, Windows, BlackBerry, Android
- IR LED: Powerful IR Led, IR Distance 30M
- Water resistance: IP66
- Lens: Board 3.6/6mm Lens (3M Pixels)



## Specifications

<b>Model No.</b>	AJB-IPC409S2-03(SU6)
<b>Resolution</b>	1080P
<b>Main Processor</b>	HI3561C(Hisilicon)
<b>Image Sensor</b>	1/2.8" CMOS SONY322
<b>Effective Pixels</b>	1920(V)*1080(H)
<b>Min. Illumination</b>	0.01lux/F1.2
<b>Video coding</b>	H.264 Main Profile coding
<b>Main Stream</b>	1280*960/1280*720, 1-30fps
<b>Sub Stream</b>	D1/CIF, 1~30fps
<b>Video Compressed</b>	0.1Mbps~6Mbps, CBR/VBR supported
<b>Subtitles Superimposed</b>	Chanel Name, Date And Time Supported
<b>Image Config</b>	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
<b>Network Interface</b>	10/100M Ethernet Port,RJ45
<b>Data Storage</b>	Video, Image Files
<b>Storage Mechanisms</b>	Manual, Auto(Cycling, Timing, Alarm switch, Motion detecting)
<b>Alarm Data Transmission</b>	Browser, Software management

<b>Protocols</b>	IPv4, TCP/IP, FTP,RTSP, RTCP, NTP, DNS, DDNS, DHCP, PPPOE, UPnP
<b>ONVIF Protocols</b>	Standard ONVIF2.4
<b>WIFI</b>	Optional, Support
<b>P2P</b>	Support
<b>POE</b>	Optional, Support IEEE 802.3af
<b>Privacy Masking</b>	Support
<b>Personal Computer</b>	IE, Firefox, Safari etc.
<b>Smart phone</b>	Smart phone and iphone Platform
<b>Lens</b>	3.6/6mm 3.0 Megapixel Lens
<b>IR Range</b>	30M
<b>IR Cut Filter</b>	Yes
<b>Operating Temperature</b>	-20°C~+60°C
<b>Operating humidity</b>	0% ~90%
<b>Power Supply</b>	DC12V
<b>Power Consumption</b>	LED off:3W / LED on: 6W
<b>Dimension</b>	∅ 115*90 mm
<b>Weight</b>	450g

Sole Distributor : Pzent Techology Company Limited