

AJB-IPC758A1-04(SU5)

Main Feature

- HD CMOS Sensor: 1/3" 1.3MP Aptinal10130
- POE/WIFI/Audio (Optional)
- ONVIF 2.4, P2P
- iPhone, Windows, BlackBerry, Android
- IR LED: 2pcs Array IR Led, IR Distance: 30M
- Water resistance: IP66
- Lens: 2.8~12mm Lens (3M Pixels)



Specifications

Model No.	AJB-IPC758A1-04(SU5)
System structure	HI3518E(Hisilicon)
Sensor	1/3" CMOS Aptinal10130
Video Processing	H.264 video coding, dual-stream, AVI form; 0.1M-6Mbps adjustable; 1-30fps adjustable;
Image Output	Main Stream: 1920*1080, 1280*720; Sub Stream: 704*576;
Network Interface	1pcs RJ45(10/100M Adaptive); RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP supported;
Lens	Varifocal 2.8~12mm Lens (3.0M)
ICR	Auto Color to B/W; ICR
IR LED	2pcs Array IR Led , IR Distance: 40M
Functions	WEB setting, OSD, Real-time browsing, Motion detection and IO alarm action (front-end storage), Front-end storage playback/download, IO alarm action (center warning and image popup), MJPEG Screenshot, Remote view (client software, MYEYE platform), Complete SDK offered

P2P	Supported
ONVIF Protocols	Standard ONVIF2.4
Mobile surveillance	Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android)
WIFI	Optional(External)
POE	Optional
Operating Temp	-10 °C - +55 °C
Operating Humidity	0% - 90%
Power Supply	DC12V
Consumption	LED off:3W / LED on: 9W
Dimension	220(L)x120(W)x70(H)mm
Weight	1.3kg

Sole Distributor : Pzent Techology Company Limited