

# AJB-IPC759A1-Z(SU2)



## Main Feature

- HD CMOS Sensor: 1/3" 1.3MP SC1035
- POE/WIFI/Audio (Optional)
- ONVIF 2.4, P2P
- iPhone, Windows, BlackBerry, Android
- IR LED: 5X36PCS, IR Distance: 30M
- Water resistance: IP66
- Lens: 2.8-12mm Lens (3M Pixels)

## Specifications

<b>Model No.</b>	AJB-IPC759A1-Z(SU2)
<b>System structure</b>	Embedded RTOS design, dual-core 32-bit DSP (Hi3516C), pure hardware compression, watchdog;
<b>Sensor</b>	1/3" SC1035 Low Illumination: Color 0.01Lux@F1.2, B/W 0.001 Lux@F1.2,
<b>Video Processing</b>	H.264 video coding, dual-stream, AVI form; 0.1M-6Mbps adjustable; 1-30fps adjustable;
<b>Image Output</b>	Main Stream: 1920*1080, 1280*720; Sub Stream: 704*576;
<b>Network Interface</b>	1pcs RJ45(10/100M Adaptive); RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP supported;
<b>Lens</b>	Varifocal 2.8~12mm Lens (3.0M)
<b>ICR</b>	Auto Color to B/W; ICR
<b>IR LED</b>	IR LED:5x36pcs, Max-IR distance:30M
<b>Functions</b>	WEB setting, OSD, Real-time browsing, Motion detection and IO alarm action (front-end storage), Front-end storage playback/download, IO alarm action (center warning and image popup), MJPEG Screenshot, Remote view (client software, MYYE platform), Complete SDK offered

<b>P2P</b>	Supported
<b>ONVIF Protocols</b>	Standard ONVIF2.4
<b>Mobile surveillance</b>	Support( iPhone, Windows Mobile, BlackBerry, Symbian, Android)
<b>WIFI</b>	Optional(External)
<b>POE</b>	Optional
<b>Operating Temp</b>	-10 °C - +55 °C
<b>Operating Humidity</b>	0% - 90%
<b>Power Supply</b>	DC12V
<b>Consumption</b>	LED off:3W / LED on: 7W
<b>Dimension</b>	300(L)x70(W)x70(H)mm
<b>Weight</b>	0.775kg

Sole Distributor : Pzent Techology Company Limited