

Special Accessories

Liquid Level Regulators - All models are non-mercury structure for earth environment.

LC "Level Switch"



MS "Mini Switch"



FV "Oval Float"



Features

LC Useful for drinking water, waste water and sewage containing the suspended solids. Hardly affected by corrosion or rust even if it is immersed in a corrosive liquid for a long time.

MS Useful for waste water and sewage containing a few suspended solids. The MS is available in two types, MS11 (single float) and MS21 (double float).

FV Useful for the fresh water as well as waste water not containing suspended solids. A single FV is able to control both the upper and lower liquid levels.

Specifications

Model	LC12	MS11, MS21	FV11
Switch	Micro Switch	Lead Switch	Lead Switch
Specific gravity of liquid	0.95~1.15	0.95~1.10	0.95~1.10
Liquid Temp	0~60°C	0~40°C	0~60°C
Voltage	AC/DC30V or under		
Current	5A or under	0.5A or under	0.6A
Cable Length	6m, 13m, 20m, 30m, 40m, 50m (further cable extension at interval of 10m)		
Cable Type	0.75mm ² ×3 cores, Flat Type	0.2mm ² ×2 cores×φ4.7mm	0.5mm ² ×2 cores×φ5.8mm
Weight (including cable)	1.2kg (6m cable)	0.6kg (MS11, 6m cable)	1.0kg (6m cable)
Material	Case	Polypropylene resin	ABS resin
	Cable	VCTFK	PVC resin (soft type)
	Others	Chain: SUS304	Sinker: Cast iron with PVC resin coating

Specifications and dimensions are subject to change without notice.

ShinMaywa Industries, Ltd.

International Business Group
Sales & Marketing Dept., Fluid Div.

3-2-43, Shitte, Tsurumi-ku, Yokohama, 230-0003, Japan
Phone : +81-45-584-1322 Fax : +81-45-575-2286
E-mail : sales.eisui@shinmaywa.co.jp

ShinMaywa (America), Ltd.

10737 Gateway West, Suite 240,
El Paso, Texas 79935, U.S.A.
Phone : +1-915-594-9862
Fax : +1-915-594-9866
E-mail : info@shinmaywaamerica.com

ShinMaywa (Asia) Pte. Ltd.

8 Burn Road, #14-10 Trivex,
Singapore 369977
Phone : +65-6224-0728
Fax : +65-6224-9678
E-mail : asia.ad@shinmaywa.com.sg

ShinMaywa (Shanghai) Trading Co., Ltd.

201107 Building 6, Lane 333, Zhujian Road,
Minhang District, Shanghai, China
Phone : +86-21-5296-2966
Fax : +86-21-5296-2970
E-mail : shanghai@shinmaywa.co.jp



ShinMaywa ONO PLANT

ISO 9001(No.956445)/ISO 14001(No.771888)