

CABLE STRUCTURE

- Conductor** : Non-compacted and compacted round annealed copper
Sizes 1.5 mm² up to 630 mm²
- Insulation** : Cross-Linked polyethylene (XLPE) with Low smoke and Zero halogen
- Core identification**
Single-cores : Black or Orange

TECHNICAL DATA

- Classification** : Maximum conductor temperature 90 °C
: Circuit voltage not exceeding 450/750 Volts
- Rated voltage** : 450 Volts between Line to Earth
: 750 Volts between Line to Line
- Testing voltage** : 2,500 Volts
- Reference standard**
: BS EN 50525-3-41, BS EN 60228, BS EN 60332-1, BS EN 60332-3-24 (Cat.C), BS EN 50267-2-2, BS EN 61034-2



APPLICATION

For fixed installation in electrical cabinet, conduit and wire way which provide flame retardant, low smoke and non toxic emission under fire.

B

Nominal cross sectional area (mm ²)	Conductor type	Insulation thickness nominal (mm)	Overall diameter approx. (mm)	Conductor resistance at 20°C maximum (Ω/km)	Insulation resistance at 90°C minimum (MΩ·km)	Continuous current rating in free air at 40°C maximum (A)	Cable weight approx. (kg/km)	Standard Length (m)
1.5	Non-Compacted	0.7	3.2	12.1	0.0100	29	22	1000/D
2.5	Non-Compacted	0.8	4.0	7.41	0.0090	39	35	1000/D
4	Non-Compacted	0.8	4.5	4.61	0.0077	52	50	1000/D
6	Non-Compacted	0.8	5.1	3.08	0.0065	66	70	1000/D
10	Compacted	1.0	6.0	1.83	0.0065	90	110	1000/D
16	Compacted	1.0	7.0	1.15	0.0050	120	170	1000/D
25	Compacted	1.2	8.6	0.727	0.0050	161	260	1000/D
35	Compacted	1.2	9.7	0.524	0.0043	199	360	1000/D
50	Compacted	1.4	11.5	0.387	0.0043	243	480	1000/D
70	Compacted	1.4	13.0	0.268	0.0035	308	650	1000/D
95	Compacted	1.6	15.5	0.193	0.0035	385	950	1000/D
120	Compacted	1.6	17.0	0.153	0.0032	449	1,200	1000/D
150	Compacted	1.8	18.5	0.124	0.0032	515	1,500	1000/D
185	Compacted	2.0	21	0.0991	0.0032	598	1,800	1000/D
240	Compacted	2.2	24	0.0754	0.0032	716	2,400	1000/D
300	Compacted	2.4	26	0.0601	0.0030	830	3,000	1000/D
400	Compacted	2.6	29	0.0470	0.0028	970	3,800	1000/D
500	Compacted	2.8	33	0.0366	0.0028	1138	4,900	500/D
630	Compacted	2.8	37	0.0283	0.0025	1333	6,000	500/D

D : Packing in drum



CABLE STRUCTURE

- Conductor** : Non-compacted and compacted round annealed copper
Sizes 1.5 mm² up to 630 mm²
- Insulation** : Cross-Linked polyethylene (XLPE) with Low smoke and Zero halogen
- Core identification**
Single-cores : Black or Orange

TECHNICAL DATA

- Classification** : Maximum conductor temperature 90 °C
: Circuit voltage not exceeding 450/750 Volts
- Rated voltage** : 450 Volts between Line to Earth
: 750 Volts between Line to Line
- Testing voltage** : 2,500 Volts
- Reference standard**
: BS EN 50525-3-41, BS EN 60228, BS EN 60332-1, BS EN 60332-3-24 (Cat.C), BS EN 50267-2-2, BS EN 61034-2

APPLICATION

For fixed installation in electrical cabinet, conduit and wire way which provide flame retardant, low smoke and non toxic emission under fire.

Nominal cross sectional area (mm ²)	Conductor type	A.C.Resistance R (Ω/km)	Inductance L (mH/km)	Reactance XL (Ω/km)	Impedance Z (Ω/km)
1.5	Non-Compacted	15.4287	0.5276	0.1657	15.4296
2.5	Non-Compacted	9.4485	0.5253	0.1650	9.4499
4	Non-Compacted	5.8782	0.5013	0.1575	5.8803
6	Non-Compacted	3.9273	0.4860	0.1527	3.9303
10	Compacted	2.3335	0.4844	0.1522	2.3384
16	Compacted	1.4664	0.4674	0.1468	1.4738
25	Compacted	0.9271	0.4630	0.1455	0.9384
35	Compacted	0.6683	0.4544	0.1427	0.6834
50	Compacted	0.4937	0.4430	0.1392	0.5129
70	Compacted	0.3420	0.4339	0.1363	0.3682
95	Compacted	0.2465	0.4343	0.1364	0.2817
120	Compacted	0.1956	0.4260	0.1338	0.2370
150	Compacted	0.1588	0.4261	0.1339	0.2077
185	Compacted	0.1272	0.4263	0.1339	0.1847
240	Compacted	0.0972	0.4225	0.1327	0.1645
300	Compacted	0.0780	0.4210	0.1323	0.1536
400	Compacted	0.0616	0.4192	0.1317	0.1454
500	Compacted	0.0488	0.4168	0.1309	0.1398
630	Compacted	0.0388	0.4122	0.1295	0.1352

B