



Leakage distance, mm	699
Protected creepage distance (mm)	356
Cantilever strength, kN	12.5
Cantilever proof load, kN	5
Low - frequency dry flashover, kV	120
Low - frequency wet flashover, kV	85
Critical - impulse flashover, positive, kV	210
Critical - impulse flashover, negative, kV	230
Low - frequency test voltage, rms to ground, kV	30
Maximum RIV at 1,000 kHz, microvolts	200
Colour of insulator glazed	Brown

INSULATOR, PIN - POST TYPE ACCORDING TO TIS. 1251, TYPE 56 / 57 - 3 L

SCALE : NTS.	UNIT: mm.	ISSUE :	DRAWN : <i>BoRE</i>	APPROVED : <i>BoRE</i>
--------------	-----------	---------	---------------------	------------------------

MANAGEABLE INSULATOR COMPANY DATE: 2 / 12 / 2013 CATALOGUE NO. PP - 573 DRAWING NO. FAC - 014



FAC

THAILAND



TIS.1251 - 2537

YEAR

บริษัท یمان จำกัด
MAN
 MANAGEABLE
 INSULATOR CO., LTD.

MARKING ON INSULATOR PIN - POST TIS 1251 - 2537 CLASS 56 / 57 - 3

SCALE : NTS. UNIT:

ISSUE :

DRAWN : *Sur*

MANAGEABLE INSULATOR COMPANY

DATE: 17 / 3 / 2014

CATALOGUE NO. PP-573

APPROVED : *enit*

DRAWING NO. FAC - 030-1