



FEATURES

- Support AHD/TVI/CVI/CVBS/IP Cameras
- Support AHD cameras up to 5MP
- Support Smart Detection & Smart Playback
- Support Extra IP Channels
- Support H.265+/H.265/H.264+/H.264
- Support Time Division & Instant Playback
- Support Google Drive & Dropbox Cloud storage

SPECIFICATION

System	
Model	WXR82108P
Video and Audio Input	
Video Input	8ch BNC interface(1.0Vp-p, 75 Ω)
TVI	5MP,4MP,1080P, 720P
CVI	5MP,4MP,1080P, 720P
AHD	5MP,4MP,1080P, 720P
IPC	2CH 2MP in default mode; Up to 5MP in full IP mode
CVBS	Support
Audio Input	1ch, RCA(2.0 Vp-p, 1 kΩ)
Two way talk	1-ch, multiplex with Audio Input(RCA)
Video and Audio Output	
HDMI	1ch, resolution : 4K(3840×2160)/30Hz,1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz,1024×768/60Hz
VGA	1ch, resolution: 1920×1080/60Hz , 1280×1024/60Hz , 1280×720/60Hz , 1024×768/60Hz
CVBS output	Support
Audio Output	1-ch, RCA (Linear, 1kΩ)
Recording	
Compression	H.265+/H.265/H.264+/H.264
Resolution	8ch 5MP Lite/1080P@12fps;
Frame rate	1-15fps
Video Bit Rate	11Kbps-8192Kbps
Audio Compression	G.711a
Audio Bit Rate	64kbps
Playback & Backup	
Playback Mode	Smart Playback/Normal/Time Division/ Label/ Event/ Picture Playback
Playback Rate	8ch Playback
Backup Mode	USB Device/Network
Advanced Features	
Smart Detection for Analog	4CH line crossing detection, intrusion detection
VQD	4CH Defocus Detection
Smart Detection for QV IPC	Line crossing detection, Area Intrusion detection
Smart Playback for Analog	Line Crossing/Area Intrusion /Motion Detection
Smart Playback for QV IPC	Line Crossing/Area Intrusion/Motion Detection
Cloud Storage	Support
Cloud Upgrade	Support
Network	
Ethernet	1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface
Network Function	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP, UDP, SMTP, SNMP, Multicast, IGMP, NTP, DHCP,DNS,DDNS, FTP, P2P
Smart Phone	IOS(iPhone, iPad), Android(Phone, Pad)
Hard Disk	
SATA	1 HDD
Capacity	Up to 10TB capacity for each HDD
External Interface	
Serial Interface	RS-485
USB Interface	2 × USB 2.0
Alarm Input /Output	NA
General	
Power Supply	DC12V,1.5A
Power Consumption	≤15W(without HDD)
Working Environment	-10°C~+55°C / 10%~90%RH
Dimension (W×D×H)	250 x 230 x 45mm
Weight(with Out HDD)	1.5kg

