

Compressed fiber sheet gasket : Model VALQUA No.6500



Product name : Compressed Fiber Sheet for General Use

Feature 1 :

These are suitable to be used as Non-asbestos gaskets for pipe flanges and equipment in various industries.

Feature 2 :

Pipe flanges, valve bonnets and other equipment used in various industries including oil refineries, chemical industries and shipyards

Applicable fluid :

Water, Sea water, Hot water, Steam, Crude oil, Alcohol, Animal & vegetable oil, Heat transfer oil, General solvent, Weak acid, Weak alkali, Air, Nitrogen gas, Inert gas, Exhaust gas, etc.

Inappropriate fluid:

Strong oxidizing acid, Strong alkali, various solvents, Inflammable gas, Gas susceptible to burn, Poisonous, etc.

Application:

Pipe flanges, valve bonnets and other equipment used in various industries including oil refineries, chemical industries and shipyards.

Main ingredient:

NBR, Aramid yarn, Mineral wool, Inorganic fillers.

Color/Print:

Blue/Black

Temperature (°C)	Pressure (MPa) Water based	Pressure (MPa) Oil based	Pressure (MPa) Gas based
-50~183	3.0	3.0	1.0

For service conditions exceeding 100°C, the notes on "The fluid-wise available ranges" shall be observed. Oil gas, solvent and corrosive fluid are not included, thus requiring separate consultation.