

### Applications

- Hydraulics.
- Refrigeration and air.
- Industrial automatic equipment.
- Engineering machinery.
- Filtration systems.



### Specifications

Accuracy : ±10%

Maximum operating pressure : 350 bar

Maximum operating temperature : 100°C

Connection : ¼"-1 ½" Thread

Option : alarm switch

### Z-6300 series

Model	Connection (BSP)	Range (L/min)	Max.working Pressure (Bar)	Dimensions					
				A	B	C	D	E	F
Z-6311	¼"	0.2-2	350	32	27	21	123	7	32
Z-6312	¼"	0.5-4.5	350	32	27	21	123	7	32
Z-6313	¼"	2-10	350	32	27	21	123	7	32
Z-6314	½"	2-20	350	40	32	31	165.5	12.5	44
Z-6315	½"	5-46	350	40	32	31	165.5	12.5	44
Z-6316	¾"	5-55	350	48	44	36	190	15	50
Z-6317	¾"	10-100	350	48	44	36	190	15	50
Z-6318	1 ¼" (1 ½")	20-180	350	84	79	66	210	18	79
Z-6319	1 ¼" (1 ½")	30-270	350	84	79	66	210	18	79
Z-6320	1 ¼" (1 ½")	40-360	350	84	79	66	210	18	79

### Dimensions :

