

Features

Low cost

Scales are direct reading for water

Detachable, clear acrylic scale plate mounts directly on front of metering tube.

Silk screened printing to enhance readability

Specifications

Model	Measuring range			Thread (F/BSP)	Weights (KG)	Working pressure (Mpa)	Accuracy	Working temperature °C
	GPM	LPM	LPH (optional)					
Z-4001	0.2~2	1~7	50~400	1/2"	0.2	≤0.6	±6%	≤55℃
Z-4002	0.5~5	1.8~18	100~1000	1/2"				
Z-4003	1~10	4~36	250~2400	3/4"				
Z-4004	2~20	10~70	500~4000	1"	0.65			
Z-4005	5~30	20~110	1000~6000	1"				
Z-4006	20~60	80~220	4000~13000	1½" male				
Z-4007	30~110	100~400	6000~25000	2"	1.4			
Z-4008	50~150	180~600	12000~35000	2"				
Z-4009	60~200	200~800	12000~50000	2"				

Note: NPT standard is optional of 304SS fittings.

Sizes

Unit: mm

Model	Z-4001	Z-4002	Z-4003	Z-4004	Z-4005	Z-4006	Z-4007	Z-4008	Z-4009
A	210	210	278	265	265	306	345	345	345
B	32	32	45	51	51	51	75	75	75
C	Joint (PP) or 1Cr18Ni9Ti(304SS)								
D	O-ring(Silicon rubber or fluoro rubber)					O-ring(Nitrile rubber)			
E	Blocking ring (ABS)					101 (Nylon)			
F	Float 1Cr18Ni9Ti(304SS)								
G	Guide rod (304SS)								
H	Body(Acrylic)								



304SS, NPT Connection (Option)



(Z-4006 Only)

