

ZCS-KDCA3

Data Docking Station



Features

High Performance

- 13.3" color LCD with resolution of 1920 x 1080
- Supports up to 24 units of body worn camera
- Supports up to 24TB storage

Easy to Use

- Wall-mounted and desktop design, easy to install
- Modular design, easy to upgrade system capacity
- Open slot design, compatible with all kinds of portable cameras
- Plug and play, auto charging and data transmission
- Touch screen operation

Abundant Functions and Features

- Record searching and playback
- Use password / fingerprint to request device
- Priority slot for high speed data transmission
- Built-in battery protection for sudden power-off / shut down

Specifications

	ZCS-KDCA3
System	
Operating System	Windows10
Processor	Intel N3710
Application System	Data Docking Station Management Software
RAM	4GB
User Management	Admin / User
Log Management	User login / User operation / Alarm / Update
Display	
Size	13.3"
Resolution	1920 x 1080
Touch Screen	Supported
Search & Playback	
File Type	Video, Audio, Pic, Log
Search Mode	Duration filter / Tag
Playback Resolution	1 x 1080p@30fp
Functions	Querying, Viewing, Downloading, Removing
Slot	
Default Slot	ZCS-KDCA3-6N: 6 Slots by default, supports 6 units of Body Worn Camera Supports up to 3 extended modules (6 slots per module) Applies to DSJ-U1-S, DSJ-U1-LPN and DSJ-U3-LPN
Extended Module	ZCS-KDCA1-EX6N: Extended module of ZCS-KDCA3-6N, 6 slots per module, supports 6 units of Body Worn Cameras) Applies to DSJ-U1-S, DSJ-U1-LPN and DSJ-U3-LPN
Slot Functions	Battery charging, Data transmission, Lock, Priority slot, Automatic upgrade, Time correction
Data Loading Speed	Full load: up to 4.6MB/s per slot For priority slot: up to 15MB/s
Alarm	
System Alarm Triggers	No disk / Insufficient recording space / Network disconnected
Alarm Events	Buzzer / Alarm text
Storage	
Max. Internal HDDs	3 x 3.5" hard disk drawer (1 x 4TB Hard disk included) Max. 24TB (up to 8TB/each)
Interfaces	
Ethernet	1 x Gigabite network port, RJ45 interface
Audio Out	Built-in speaker
Point lock	1 x Point lock (Unlock all devices at the same time by key)
USB	2 x USB 2.0
Environmental	
Operating Temperature	-10°C ~ 55°C / 14°F ~ 131°F
Operating Humidity	10% ~ 95%
Electrical	
Power	100 ~ 240V AC, 50 ~ 60Hz *ZCS-KDCA3-6N: Max. 105W ZCS-KDCA3-6N + 1 x ZCS-KDCA3-EX6N: Max. 135W ZCS-KDCA3-6N + 2 x ZCS-KDCA3-EX6N: Max. 165W ZCS-KDCA3-6N + 3 x ZCS-KDCA3-EX6N: Max. 195W
Power Consumption	
Emergency Power	Built-in battery: 2150mAh
Mechanical	
Weight	ZCS-KDCA3-6N: 10.3Kg / 22.7lb (HDD not included) ZCS-KDCA3-EX6N: 3.68Kg/8.11lb
Dimensions	ZCS-KDCA3-6N: 430 x 510 x 113mm / 16.92" x 20.08" x 4.45" ZCS-KDCA3-EX6N: 190 x 510 x 113mm / 7.48" x 20.08" x 4.45"

Dimensions

Units:mm

