

KTT-series



True On-line Double Conversion Modular UPS

Three Phase Input / Three Phase Output True On-line UPS

- True on-line double conversion technology
- Full DSP control
- IGBT inverter & output isolation transformer
- 3-phase UPS allow 100% unbalance load
- Full static transfer switch
- Zero time transfer switch
- Emergency Power Off function (EPO)
- N+x parallel redundancy up to 6 units
- LED indicator and large LCD display
- Intelligent battery management
- Intelligent control and monitoring system
- Built-in battery cold start unit
- Economy mode & Online mode
- RS-232 port
- SNMP/HTTP monitor capability and dry contact (option)
- Product from ISO 9001 and ISO 14001 certified factory

Applications

- Internet service provider
- Computer data center
- Industrial automation
- Bank or security system
- Telecommunication system
- Transportation system
- Mission-critical equipments



MODEL		KTT-103	KTT-203	KTT-303	KTT-403	KTT-603	KTT-803
CAPACITY	VA	10 kVA	20 kVA	30 kVA	40 kVA	60 kVA	80 kVA
	Watt	9 kW	18 kW	27 kW	36 kW	54 kW	72 kW
MAIN INPUT	Voltage	(380 / 400 / 415 Vac) : 380 Vac (L-L) ± 25%					
	Frequency	50 / 60 Hz ± 5 Hz auto sensing					
	Phase	Three phase four wires					
	Power factor	1 (with filter)					
BYPASS INPUT	Voltage	Upper limit: 380 Vac (L-L) +10%, +15%, +20% (can be set)					
		Lower limit: 380 Vac (L-L) -10%, -20%, -30%, -40% (can be set)					
OUTPUT	Voltage	(380 / 400 / 415 Vac) : 380 Vac (L-L) ± 1%					
	Transient voltage response	5%					
	Power factor	0.9					
	Frequency (battery mode)	50 Hz ± 0.05%					
	Total Harmonic Distortion	< 3% at linear load, < 5% at non-linear load					
	Overload capability	110% transfer to bypass after 1 hour, 125% transfer to bypass after 10 minutes, 150% transfer to bypass after 1 minute and > 150% transfer to bypass after 200 ms					
	Crest factor ratio	3 : 1					
EFFICIENCY	AC to AC	88%	89%	90%	90%	91%	91%
		sealed lead acid (maintenance free) rechargeable					
BATTERY	Nominal voltage	384 Vdc					
	EMI attenuation	IEC 62040-2					
STANDARD	EMS	IEC 61000-4-2 (ESD), IEC 61000-4-3 (RS), IEC 61000-4-4 (EFT), IEC 61000-4-5 (Surge)					
	Industrial standard	CE, EN / IEC 62040-2, EN / IEC 62040-1-1					
	Enclosure protection	IP20					
INDICATOR	Front panel LED	Input, Inverter, Battery, Output status					
	Front panel LCD's	Input & output voltage, frequency, power factor, battery voltage, battery current, battery status, load percentage, UPS status, history record, parameters setting					
AUDIBLE ALARM	Buzzer	yes					
COMMUNICATION INTERFACE	Standard interface	RS-232 port and RS-485 port					
	SNMP/HTTP capability	option					
	Dry contact	option					
SOFTWARE	UPS monitoring and management software	yes					
ACOUSTIC NOISE	At 1 metre	62 dBA					
ENVIRONMENT	Temperature	0 - 40°C					
	Relative humidity	0 - 95% (non-condensing)					
DIMENSIONS	W x H x D (approx. in cm.)	57 x 119.5 x 80				88 x 160 x 76	
WEIGHT	Approximate in kg.	225	275	320	335	490	575

Continuous product development is our commitment. In that manner, the above specifications may be changed without prior notice.

LEO POWER SUPPLY CO.,LTD.

27, 4th Floor, Soi Bangna-Trad Rd 34, Bangna-Trad Road, Bangna, Bangkok 10260 THAILAND
Tel. 0-2746-9500, 0-2746-8708 Fax. 0-2746-8712 e-mail : marketing@lpsups.com

M.MEX.BRO.UPS.1279 Rev.4.00/2018