

UKT-series



True On-line Double Conversion UPS

3:1 and 1:1 Phase Configuration

- True on-line double conversion with DSP control
- N+x parallel redundancy up to 4 units
- Wide input range (208 ~ 478 Vac)
- 50/60 Hz frequency converter mode
- Support 3/1 and 1/1 operation
- Self-testing when UPS startup
- ECO mode operation for energy saving
- Cold start function
- Intelligent fan speed regulation
- LED indicator and large LCD display
- Generator compatible
- Product from ISO 9001 and ISO 14001 certified factory

Applications

- Internet service provider
- Computer data center
- Industrial automation
- Bank or security system
- Telecommunication system
- Transportation system
- Mission-critical equipments



MODEL		UKT-10
CAPACITY		10 kVA / 9kW (10 kVA / 10kW optional)
INPUT	Voltage	380 / 400 / 415 Vac (3Ph+N+PE) or 220 / 230 / 240 Vac (L+N+PE)
	Voltage range	208 ~ 478 Vac (L-L) or 120 ~ 276 Vac (L-N)
	Frequency	50/60 Hz \pm 10% (auto sensing)
OUTPUT	Voltage	220 / 230 / 240 Vac (L+N+PE)
	Voltage regulation	\pm 1%
	Frequency	50 Hz \pm 0.1%
	Power factor	0.9 (1.0 is optional)
	Wave form	Pure sine wave
	Total harmonic distortion	\leq 2% of THDv at linear load, \leq 5% of THDv at non-linear load
	Overload capability	AC mode: \leq 110% for 60 min, \leq 125% for 10 min, \leq 150% for 1 min. turn to bypass. \geq 150% turn to bypass immediately Battery mode: \leq 110% for 10 min, \leq 125% for 1 min, \leq 150% for 5s, $>$ 150% shutdown immediately
	Crest factor ratio	3:1
Efficiency	94.5%	
Protection	Overload, short circuit, over heat, battery over charge / discharge, low battery voltage and fan fault alarm	
TRANSFER TIME		Zero time (True on-line UPS)
BATTERY	Type	Sealed lead acid (VRLA) (maintenance free) rechargeable
	Capacity	9Ah x 20 pcs, (9Ah x 20 pcs) x 2 is optional
	Backup time	15 - 30 minutes (depending on load)
	Extended backup time	option
INDICATOR	LED	Inverter, Battery, Bypass, Alarm
	LCD display	Input (voltage/frequency), Output (voltage/frequency), Battery (voltage/current), Load (Watt/VA), Temperature, Alarm, Bus voltage, Charger status, Operation mode
AUDIBLE ALARM	Buzzer	yes
COMMUNICATION INTERFACE	RS-232 and RS-485 port	yes
	USB port	yes
	Parallel port	option
	SNMP/HTTP capability	option
SOFTWARE	UPS monitoring and management software	option
ACOUSTIC NOISE	At 1 metre	$<$ 58 dBA
STANDARD	Safety	IEC/EN 62040-1, IEC/EN 62477-1
	EMC	IEC/EN 62040-2 (IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11, IEC 61000-2-2)
ENVIRONMENT	Temperature	0 ~ 40°C
	Relative humidity	0 ~ 95% (non-condensing)
DIMENSIONS	W x H x D (cm)	25 x 86.8 x 90 cm
WEIGHT	Approx. in kg.	180 kg

Continuous product development is our commitment. In that manner, the above specifications may be changed without prior notice.

LEO POWER SUPPLY CO.,LTD.

27, 4th Floor, Soi Bangna-Trad Rd 34, Bangna Tai, Bangna, Bangkok 10260 THAILAND
Tel. 0-2746-9500 e-mail : marketing@lpsups.com

M.MEX.BRO.UPS.1753 Rev.2.00/2025