







Summary of our stock program
Seamless Elbows (90 LR/SR/45)

Dimension accordance to: ASME/ANSI B16.9

Dimension ac Dimen		ance it	WP304/304L	•
1/2 " EL90		10S	•	•
	LR	40S	•	•
		10S		
	SR	40S		
		10S	•	•
EL45		40S	•	•
3/4 " EL90		10S	•	•
	LR	40S	•	•
		10S		
	SR	40S		
=		10S	•	•
EL45		40S	•	•
1 " EL90		10S	•	•
	LR	40S	•	•
	<b>C</b> D	10S		
	SR	40S		
FI 4F		10S	•	•
EL45		40S	•	•
1.1/4 " EL90	LR	10S	•	•
	LN	40S	•	•
	SR	10S		
	Sh	40S		
EL45		10S	•	•
EL45		40S	•	•
1.1/2 " EL90	LR	10S	•	•
	LIV	40S	•	•
	SR	10S	•	•
	OIT	40S	•	•
EL45		10S	•	•
		40S	•	•
2 " EL90	LR	10S	•	•
		40S	•	•
	SR	10S	•	•
		40S	•	•
EL45		10S	•	•
		40S	•	•
2.1/2 " EL90	LR	10S	•	•
		40S	•	•
	SR	10S	•	•
		40S	•	•
EL45		10S	•	•
		40S	•	•

Dimension		WP304/304L	WP316/316L	
3 " EL90	LD	10S	•	•
	LR	40S	•	•
	SR	10S	•	•
	SN	40S	•	•
EL45		10S	•	•
EL45		40S	•	•
4 " EL90	LR	10S	•	•
	LIN	40S	•	•
	SR	10S	•	•
	JIN	40S	•	•
EL45		10S	•	•
		40S	•	•
5 " EL90	LR	10S	•	•
	LIV	40S	•	•
	SR	10S		
	OIT	40S		
EL45		10S	•	•
		40S	•	•
6 " EL90	LR	10S	•	•
		40S	•	•
	SR	10S	•	•
	OIT	40S	•	•
EL45		10S	•	•
		40S	•	•
8 " EL90	LR	10S	•	•
		40S	•	•
	SR	10S	•	•
	JI (	40S	•	•
EL45		10S	•	•
		40S	•	•







### Summary of our stock program

Seamless TEE, TEE REDUCER, Dimension accordance to: ASME/ANSI B16.9

Dimension accordance to: ASME/ANSI B16.9

Difficultiation accordance to . Asime/Ansi b10.5				
Dimension		WP304/304L	WP316/316L	
1/2 " TEE	10S	•	•	
	40S	•	•	
3/4 " TEE	10S	•	•	
	40S	•	•	
1 " TEE	10S	•	•	
	40S	•	•	
1.1/4 " TEE	10S	•	•	
	40S	•	•	
1.1/2 " TEE	10S	•	•	
	40S	•	•	
2 " TEE	10S	•	•	
	40S	•	•	
3 " TEE	10S	•	•	
	40S	•	•	
4 " TEE	10S	•	•	
	40S	•	•	
6 " TEE	10S	•	•	
	40S	•	•	
8 " TEE	10S	•	•	
	40S	•	•	

Dimension		WP304/304L	WP316/316L
TEE REDUCE			
3/4 " x 1/2 "	10S	•	•
	40S	•	•
1" x 1/2"	10S	•	•
	40S	•	•
1 " v 0 / 4 "	10S	•	•
1"x3/4"	40S	•	•
1 1/0    1 0 / 4	10S	•	•
1.1/2 " x 3/4 "	40S	•	•
4.4/0 !! 4 !!	10S	•	•
1.1/2 " x 1 "	40S	•	•
0.114.11	10S	•	•
2"x1"	40S	•	•
0    4 4 (0	10S	•	•
2 " x 1.1/2 "	40S	•	•
0.4/0.11.4.4/0.11	10S	•	•
2.1/2 " x 1.1/2 "	40S	•	•
	10S	•	•
2.1/2 " x 2 "	40S	•	•
	10S	•	•
3"x2"	40S	•	•
	10S	•	•
3" x 2.1/2"	40S	•	•
	10S	•	•
4"x2"	40S	•	•
	10S	•	•
4" x 2.1/2"	40S	•	•
	10S	•	•
4"x3"	40S	•	•
	10S	•	•
5 " x 3 "	40S	•	•
	10S	•	•
5 " x 4 "	40S	•	•
	10S	•	•
6"x3"	40S	•	•
	10S	•	•
6"x4"	40S	•	•
	10S	•	•
6"x5"	40S	•	•
	10S	•	
8"x4"	40S	•	•
8"x6"	10S	•	
	40S	•	







Summary of our stock program

Seamless CON. REDUCER, ECC. REDUCER

Dimension accordance to: ASME/ANSI B16.9

imension accord Dimension	arroo t		WP316/316L
CON. REDUCE			_
0/4 !! 4/0 !!	10S	•	•
3/4 " x 1/2 "	40S	•	•
1" x 1/2"	10S	•	•
	40S	•	•
4 11 0 / 4 11	10S	•	•
1 " x 3/4 "	40S	•	•
1.1/2 " x 3/4 "	10S	•	•
	40S	•	•
4 4 40 11 4 11	10S	•	•
1.1/2 " x 1 "	40S	•	•
	10S	•	•
2"x1"	40S	•	•
	10S	•	•
2 " x 1.1/2 "	40S	•	•
	10S	•	•
2.1/2 " x 1.1/2 "	40S	•	•
	10S	•	•
2.1/2 " x 2 "	40S	•	•
	10S	•	•
3"x2"	40S	•	•
	10S	•	
3" x 2.1/2"	40S	•	•
	10S	•	•
4"x2"	40S	•	•
	10S	•	•
4" x 2.1/2"	40S	•	•
	10S	•	•
4"x3"	40S	•	•
	10S	•	•
5"x3"	40S	•	•
	10S	•	
5"x4"	40S	•	
	10S		
6"x3"	40S		
	10S	•	
6"x4"	40S		
	10S		
6"x5"	40S	•	•
	40S	•	
8"x4"	40S	•	•
	40S 10S	•	
8"x6"		•	•
	40S	•	

Dimensio	n	WP304/304L	WP316/316L
ECC. REDUCE			
3/4 " x 1/2 "	10S	•	•
3/4 X 1/2	40S	•	•
1 " x 1/2 "	10S	•	•
	40S	•	•
1"x3/4"	10S	•	•
1 7 0/4	40S	•	•
1.1/2 " x 3/4 "	10S	•	•
1:1/2 X 0/4	40S	•	•
1.1/2 " x 1 "	10S	•	•
1.1/2 X 1	40S	•	•
2"x1"	10S	•	•
	40S	•	•
2 " x 1.1/2 "	10S	•	•
	40S	•	•
2.1/2 " x 1.1/2 "	10S	•	•
	40S	•	•
2.1/2 " x 2 "	10S	•	•
	40S	•	•
3"x2"	10S	•	•
	40S	•	•
3 " x 2.1/2 "	10S	•	•
	40S	•	•
4"x2"	10S	•	•
	40S	•	•
4" x 2.1/2"	10S	•	•
. , , , , , , , , , , , , , , , , , , ,	40S	•	•
4"x3"	10S	•	•
	40S	•	•
5"x3"	108	•	•
	40\$	•	•
5"x4"	108	•	•
	40\$	•	•
6"x3"	10S	•	•
	40S	•	•
6"x4"	10S	•	•
	40S	• -	-
6"x5"	10S	•	•
	40S	•	•
8 " x 4 "	10S	•	•
	40S	•	•
8"x6"	10S	•	•
	40S	•	•







#### Summary of our stock program

#### Seamless CAP

Dimension accord	dance to	o : ASME/ANSI	B16.9
Dimension	1	WP304/304L	WP316/316L
1/2 "	10S	•	•
	40S	•	•
3/4 "	10S	•	•
	40S	•	•
1"	10S	•	•
	40S	•	•
1.1/4 "	10S	•	•
1.1/4	40S	•	•
1.1/2 "	10S	•	•
1.1/2	40S	•	•
2 "	10S	•	•
	40S	•	•
2.1/2 "	10S	•	•
2.1/2	40S	•	•
3"	10S	•	•
3	40S	•	•
4 "	10S	•	•
4	40S	•	•
5 "	10S	•	•
	40S	•	•
6 "	10S	•	•
	40S	•	•
8 "	10S	•	•
	40S	•	•

#### Seamless STUB END

Dimension accordance to: MSS SP-44 SHORT PATTERN WP304/304L WP316/316L Dimension 10S 1/2 " **40S** 10S • • 3/4" 40S 10S 1 " 40S 10S • 1.1/4" **40S 10S** 1.1/2 " **40S** • 10S 2" **40S** • • 10S 2.1/2 " 40S 10S • 3 " **40S** 10S • • 4 " 40S 10S 5 " 40S 10S • 6" 40S 10S 8 "

**40S** 

•