


**CREALITY : 3D Printer****CREALITY**

Model	CR-10 Max	CR-10 Smart	CR-30
Molding Tech	FDM (Fused Deposition Molding)	FDM (Fused Deposition Molding)	FDM (Fused Deposition Molding)
Filament	PLA	PLA / ABS / TPU / PETTG	PLA / TPU / PETG
Hotbed Temp	≤100 C	≤100 C	≤100 C
File Transfer	TF Card/USB	SD Card / Wifi	USB / SD Card
Language	English / Chinese	9 language	Chinese / English
File Format	STL/OBJ/AMF	STL/OBJ/AMF	STL/OBJ/AMF
Slice Software	Creality Slicer / Cura / Repetier - Host / Simplify3D	Creality / Cura	CrealityBelt
Operation System	Window XP / 7 / 8 / 10 Mac / Linux		0.1mm - 0.4mm
Power Supply	RV : 100 - 240 V , Output : 24V	RV : 100 - 240 V , Output : 24V	RV: 100-120V / 200-240V , Output : 24V
Nominal Power	750W	1.75 mm	1.75mm
Machine Size	650 x 785 x 735 mm 20 Kg	578 x 522 x 648 mm 14 Kg	535 x 656 x 410 mm 16.5 Kg
SRP(inc.VAT)	33,990.-	16,290.-	46,590.-




Model	CR-200B	CR-3040 Pro	Ender 3 Max
Molding Tech	FDM (Fused Deposition Molding)	FDM (Fused Deposition Molding)	FDM (Fused Deposition Molding)
Filament	PLA / ABS	PLA / ABS	PLA / PETG / ABS
Hotbed Temp	≤100 C	≤100 C	≤100 C
File Transfer	USB / SD Card	USB / SD Card	TF Card / USB
Language	Chinese / English	Chinese / English	Chinese / English
File Format	STL/OBJ/AMF	STL/OBJ/AMF	STL / OBJ / AMF
Slice Software	Creality Slicer / Cura / Repetier - Host / Simplify3D	Creality Slicer / Cura / Repetier - Host / Simplify3D	Creality Slicer / Cura / Repetier - Host / Simplify3D
Operation System	WIN / XP / MAC / Linux / Vista	WIN / XP / MAC / Linux / Vista	WIN / XP / MAC / Linux / Vista
Power Supply	RV : 115 - 235V . Out put : 24V	RV : 115 - 230 V , Output : 24V	Rated Voltage : 115V - 230V Output : 24V
Nominal Power	350W	500W	350W
Machine Size	411 x 435 x 503 mm 16 Kg	580 x 471 x 885 mm 58 Kg	513 x 563 x 590 mm 9.5 Kg
SRP(inc.VAT)	16,290.-	64,590.-	11,890.-




Model	Ender 3 V2	Ender 3
Molding Tech	FDM (Fused Deposition Molding)	FDM (Fused Deposition Molding)
Filament	PLA / PETG / ABS / TPU	PLA / TPU / Wood / Carbon Fiber . etc.
Hotbed Temp	≤100 C	≤100 C
File Transfer	USB / TF Card	USB / TF Card
Language	Chinese / English	Chinese / English
File Format	STL / OBJ / AMF	STL / OBJ / AMF
Slice Software	Creality Slicer / Cura / Repetier - Host / Simplify3D	Creality Slicer / Cura / Repetier - Host / Simplify3D
Operation System	WIN / XP / MAC / Linux / Vista	WIN / XP / MAC / Linux / Vista
Power Supply	RV : 115 / 230V Output 24V	RV : 115 / 230V Output 24V
Nominal Power	350W	270W
Machine Size	475 x 470 x 473 mm 7.8 Kg	440 x 440 x 465 mm 6.62 Kg
SRP(inc.VAT)	9,890.-	6,490.-

**CREALITY : 3D Printer**

**CREALITY**



Layer Thickness  
0.1mm - 0.6mm



Model	Ender-7	K8	Sermoon D1
Molding Tech	FDM (Fused Deposition Molding)	FDM (Fused Deposition Molding)	FDM (Fused Deposition Molding)
Filament	PLA / PETG / ABS	Light - Transmitting / Shading Material (Filament)	PLA / ABS / TPU
Hotbed Temp	≤100 C	≤65 C	≤100 C
File Transfer	USB Cable / TF Card	USB / SD Card	Online or SD Card
Language	CH / EN / Spanish / German / French / Russian	Chinese	Chinese / English
File Format	STL / OBJ / AMF	STL / OBJ / AMF	STL / OBJ / AMF
Slice Software	Creality Slicer / Cura / Repetier - Host / Simplify3D		Creality Slicer / Cura / Repetier - Host / Simplify3D
Operation System	Windows XP / Vista / 7 / 10 MAC Linux	Win 7 / Win 10 64 bits	WIN / XP / MAC / Linux / Vista
Power Supply	RV100 - 120V / 200 - 240V Output 24V	RV : 100 -240V , Output 24V	AC 100 - 240V , DC 24V
Nominal Power	350W	1.8KW	
Machine Size	430 x 460 x 570 mm 17.2 Kg	1222 x 1130 x 700 mm 65 Kg	500 x 500 x 531 mm 20.5 Kg
SRP (inc.VAT)	24,790.-	112,000.-	26,490.-



Model	Halot Sky
Molding Tech	LCD resin Curing
Filament	405 mm Photosensitive Resin
Print Speed	1 - 4 / s layer
Operation interface	Support 12 Language (Chinese / English preferred)
XY - Axis Precision	0.05 mm
Layer Thickness	0.01 - 0.2 mm
Display Screen	5 - inch Full - Color Touch Screen
Light Source	Integrate light Source
Z - Axis Type	Dual linear Guid Raiks + Ball Screws
Trough	Compatible with LD - 006 Trough
Machine Size	340 x 202 x 552 mm 16.5 Kg
SRP (inc.VAT)	38,790.-



Model	Halot one
Molding Tech	LCD resin Curing
Print Filament	Photosensitive Resin
Print Precision	1 - 4 / s layer
Print Method	Chinese / English
Operation interface	405 mm
Supported Formant	5.0 Capacitive layer
Print Speed	0.051 mm
Operation System	Windows 7 an above
Power Requirement	Rated Voltage : 100 - 240V , Output : 24V
Rated Power	100W
Machine Size	221 x 221 x 494 mm 7.1 Kg
SRP (inc.VAT)	9,890.-

**เครื่องพักชิ้นงาน**



Model	UW - 02
Washing and Curing	2 / 5 / 10 / 15 / 20 / 30 mins
Machine Function	Washing and Curing
Speed	Regular / Fast
Power Requirement	RV : 100 -240V , Output 24V
Rated Power	60W
Supported language	Chinese / English
Operation System	Windows 7 and above
Washing Basket	304 Stainless Steel
Curing Platform	Mirror Stainless Steel
Machine Size	325 x 295 x 485 mm 9 Kg
SRP (inc.VAT)	7,490.-

**CREALITY : Spare Part****CREALITY**

SIS Part No.	Creality	SRP (Inc.VAT)
CLT-4008050016	CR Scan 01 upgraded	27,750
CLT-4001050011	Ender-3 Screen Kit	513
CLT-4004090015	Platform Sticker	205
CLT-4004070007	Thermistor Cable	52
CLT-4001010005	Auto Leveling Sensor 8 Bit/BL Touch	1,947
CLT-4001040003	Hotbed Kit	533
CLT-4001070002	Pulley Kit	72
CLT-4001080033	Ender-3 Y Axis Timing Belt Kit	72
CLT-4004090035	Carborundum platform glass board	287
CLT-4004090014	Carborundum Glass Platform 310x320	462
CLT-4001040002	Hotbed kit	1,128
CLT-4001050009	Ender-3 Max Screen Kit	1,107
CLT-4004090031	Carborundum Glass Platform Ender-3V2	287
CLT-4004180004	Limit Switch Kit	63
CLT-4002020012	Ender-3 V2 Slient Motherboard	1,640
CLT-4003010006	Dual Screw Upgrade Package	1,177
CLT-4004070012	Thermistor Kit	72
CLT-4001040019	Hotbed Kit Ender 3 V2 235x235	564
CLT-4001010009	End-3V2 BL Touch Auto Leveling Kit 32Bit	1,721
CLT-4001070004	Pulley Kit	205
CLT-4004010063	Memory card	257
CLT-4001040025	Hotbed Plate Kit	1,282
CLT-4004070004	Thermistor	42
CLT-4001080023	Timing Belt Kit L 1220mm Ender 5 Plus	94
CLT-4001050037	Screen Kit	2,357
CLT-4001040039	Hotbed Kit	2,868
CLT-4001090010	Filament Sensor Kit	257
CLT-4001050008	Screen Kit	1,004
CLT-4001040001	Platform Kit	3,278
CLT-4004070009	NTC	52
CLT-4004010129	CR-30 Belt Kit	2,562
CLT-4001040015	Hotbed Board Kit	1,895
CLT-4004070001	Nozzle Thermistor	52
CLT-4001050036	Screen Kit	2,050
CLT-4001090010	Filament Sensor Kit	226
CLT-4004090065	Carborundum Glass Platform Board	410
CLT-4001090010	Filament Sensor Kit	257
CLT-4001050017	Screen	1,282
CLT-4001040024	Hotbed Kit	1,282
CLT-4004090045	CR-200B carborundum glass plate	329
CLT-4004070015	Thermistor	63
CLT-4004120012	Synchronous Wheel Kit	124
CLT-4004180016	limit switch Module	33
CLT-4001090010	Filament Sensor Kit	257
CLT-4001050024	Display screen	2,357
CLT-4001040026	Hotbed Board Kit	1,128
CLT-4004090059	Carborundum Glass Platform	462
CLT-4004070019	Thermistor	42
CLT-4004090059	Carborundum Glass Platform	410
CLT-4004010071	Resin Vat Kit	1,434
CLT-4001050038	Touch Screen Kit	1,741
CLT-4004010002	Air Filter Fan Cover	103

**CREALITY : Consumable****CREALITY**

SIS Part No.	Creality	SRP (Inc.VAT)
CLT-3301010040	HP-PLA White 1.75mm 1KG	646
CLT-3301010041	HP-PLA Black 1.75mm 1KG	646
CLT-3301010039	HP-PLA Grey 1.75mm 1KG	646
CLT-3301010034	HP-PLA Orange 1.75mm 1KG	646
CLT-3301010038	HP-PLA Red 1.75mm 1KG	646
CLT-3301010036	HP-PLA Yellow 1.75mm 1KG	646
CLT-3301010037	HP-PLA Blue 1.75mm 1KG	646
CLT-3301010035	HP-PLA Green 1.75mm 1KG	646
CLT-3301010061	CR-PLA Black 1.75mm 1KG	636
CLT-3301010066	CR-PLA Grey 1.75mm 1KG	636
CLT-3301010024	CR-PLA Sapphire blue 1.75mm 1KG	636
CLT-3301010120	CR-PLA Grass Green 1.75mm 1KG	636
CLT-3301010069	CR-PLA Orange 1.75mm 1KG	636
CLT-3301010068	CR-PLA Pink 1.75mm 1KG	636
CLT-3301010062	CR-PLA Red 1.75mm 1KG	636
CLT-3301010063	CR-PLA Yellow 1.75mm 1KG	636
CLT-3301010121	Ender-PLA White 1.75mm 1KG	513
CLT-3301010122	Ender-PLA Black 1.75mm 1KG	513
CLT-3301010123	Ender-PLA Grey 1.75mm 1KG	513
CLT-3301010124	Ender-PLA Red 1.75mm 1KG	513
CLT-3301010126	Ender-PLA Yellow 1.75mm 1KG	513
CLT-3301010125	Ender-PLA Blue 1.75mm 1KG	513
CLT-3301020012	CR-ABS White 1.75mm 1KG	466
CLT-3301020013	CR-ABS Orange 1.75mm 1KG	466
CLT-3301020016	CR-ABS Pink 1.75mm 1KG	466
CLT-3301020008	CR-ABS Black 1.75mm 1KG	466
CLT-3301020014	CR-ABS Red 1.75mm 1KG	466
CLT-3301020010	CR-ABS Yellow 1.75mm 1KG	466
CLT-3301020007	CR-ABS Grey 1.75mm 1KG	466
CLT-3301020011	CR-ABS Blue 1.75mm 1KG	466
CLT-3301020009	CR-ABS Green 1.75mm 1KG	466
CLT-3301020015	CR-ABS Brown 1.75mm 1KG	466
CLT-3301040010	CR-TPU White 1.75mm 1KG	855

## CREALITY : Consumable

CREALITY

SIS Part No.	Creality	SRP (Inc.VAT)
CLT-3301040003	CR-TPU Orange 1.75mm 1KG	855
CLT-3301040002	CR-TPU Pink 1.75mm 1KG	855
CLT-3301040009	CR-TPU Black 1.75mm 1KG	855
CLT-3301040008	CR-TPU Red 1.75mm 1KG	855
CLT-3301040004	CR-TPU Yellow 1.75mm 1KG	855
CLT-3301040005	CR-TPU Grey 1.75mm 1KG	855
CLT-3301040011	CR-TPU Blue 1.75mm 1KG	855
CLT-3301040006	CR-TPU Green 1.75mm 1KG	855
CLT-3301040001	CR-TPU Brown 1.75mm 1KG	855
CLT-3302010007	Water Resin, 1kg, White, Alu Can	1,434
CLT-3302010008	Water Resin, 1kg, Yellow, Alu Can	1,434
CLT-3302010009	Water Resin, 1kg, Transp blue, Alu Can	1,434
CLT-3302010010	Water Resin, 1kg, skin color, Alu Can	1,434
CLT-3302010011	Water Resin, 1kg, grey, Alu Can	1,434
CLT-3302010012	Water Resin, 1kg, black, Alu Can	1,434
CLT-3302010013	Water Resin, 1kg, purple, Alu Can	1,434
CLT-3302010014	Water Resin, 1kg, Transp, Alu Can	1,434
CLT-3302010015	Water Resin, 1kg, Transp red, Alu Can	1,434
CLT-3302010016	Water Resin, 1kg, Transp green, Alu Can	1,434
CLT-3302010001	Water Resin, 500g, purple, Alu Can	739
CLT-3302010002	Water Resin, 500g, transpaent, Alu Can	739
CLT-3302010017	Water Resin, 500g, White, Alu Can	739
CLT-3302010020	Water Resin, 500g, skin color, Alu Can	739
CLT-3302010021	Water Resin, 500g, grey, Alu Can	739
CLT-3302010022	Water Resin, 500g, black, Alu Can	739
CLT-3302010003	Water Resin, 500g, Transp red, Alu Can	739
CLT-3302010004	Water Resin, 500g, Transp green, Alu Can	739
CLT-3302010018	Water Resin, 500g, Yellow, Alu Can	739
CLT-3302010019	Water Resin, 500g, Transp blue, Alu Can	739
CLT-3302030009	Low Odor Resin, 1kg, grey, Alu Can	1,107
CLT-3302030015	Low Odor Resin, 1kg, Transp green, Alu Can	1,107
CLT-3302030016	Low Odor Resin, 1kg, yellow, Alu Can	1,107
CLT-3302030017	Low Odor Resin, 1kg, blue, Alu Can	1,107
CLT-3302030018	Low Odor Resin, 1kg, black, Alu Can	1,107
CLT-3302030019	Low Odor Resin, 1kg, orange, Alu Can	1,107
CLT-3302030020	Low Odor Resin, 1kg, green, Alu Can	1,107
CLT-3302030021	Low Odor Resin, 1kg, skin color, Alu Can	1,107
CLT-3302030022	Low Odor Resin, 1kg, Transp, Alu Can	1,107
CLT-3302030023	Low Odor Resin, 1kg, Transp red, Alu Can	1,107
CLT-3302030024	Low Odor Resin, 1kg, red, Alu Can	1,107
CLT-3302030026	Low Odor Resin, 1kg, White, Alu Can	1,107
CLT-3302030027	Low Odor Resin, 1kg, Transp blue, Alu Can	1,107
CLT-3302030002	Low Odor Resin, 500g, Transp, Alu Can	555
CLT-3302030003	Low Odor Resin, 500g, skin, Alu Can	555
CLT-3302030012	Low Odor Resin, 500g, Grey, Alu Can	555
CLT-3302030013	Low Odor Resin, 500g, White, Alu Can	555
CLT-3302030001	Low Odor Resin, 500g, Transp Red, Alu Can	555
CLT-3302030004	Low Odor Resin, 500g, Green, Alu Can	555
CLT-3302030005	Low Odor Resin, 500g, Orange, Alu Can	555
CLT-3302030006	Low Odor Resin, 500g, Black, Alu Can	555
CLT-3302030007	Low Odor Resin, 500g, Blue, Alu Can	555
CLT-3302030008	Low Odor Resin, 500g, Yellow, Alu Can	555
CLT-3302030010	Low Odor Resin, 500g, TranspGreen, Alu Can	555
CLT-3302030011	Low Odor Resin, 500g, Transp Blue, Alu Can	555
CLT-3302030025	Low Odor Resin, 500g, Red, Alu Can	555
CLT-3302020053	STD. Rigid Resin, 1kg, grey, Alu Can	974
CLT-3302020055	STD. Rigid Resin, 1kg, black, Alu Can	974
CLT-3302020056	STD. Rigid Resin, 1kg, Transp, Alu Can	974
CLT-3302020057	STD. Rigid Resin, 1kg, skin, Alu Can	974
CLT-3302020059	STD. Rigid Resin, 1kg, Transp Red, Alu Can	974
CLT-3302020060	STD. Rigid Resin, 1kg, Transp Blue, Alu Can	974
CLT-3302020061	STD. Rigid Resin, 1kg, Transp Green, Alu Can	974



## เส้นใยชนิดต่างๆ

1. พลาสติก PLA
  2. พลาสติก ABS
  3. พลาสติก TPU แบบยืดหยุ่น
- เป็นเส้นใยพลาสติกคุณภาพสูงที่สามารถย่อยสลายได้  
และไม่ก่อให้เกิดมลพิษ มาในลักษณะเป็นม้วน

Technical Date	CR - PLA
Diameter	1.75 mm
Net Weight	1 Kg
Printing Temp	195 - 210 C
Bed	45 - 55 C
Impact Strength	≥ 3%
Tensile Strength	≥ 60 Mpa
Specific Gravity	1.25 ± 0.05g/cm3
Solution Flow Velocity	5 - 7 g/10 min
Hydroscopicity	0.50%



## พลาสติก Resin

เป็นพลาสติกที่เคลือบบรรจุขวด

High hardness with good toughness  
High printing speed  
Low shrinkage rate  
Almost odorless and non - toxic  
High hardness of 88D  
Compatible with most LCD resin printer