

Rack 2 Way 1U

Rack 2 Way 1U
Altos R360 F4

*High performance,
small footprint.*



	Altos R360 F4 ACR-USREBST001	Altos R360 F4 ACR-USREAST005
CPU Types	1 x Intel® Xeon® Silver 4110 Processor 11M Cache, 2.10 GHz	1 x Intel® Xeon® Silver 4114 Processor 13.75M Cache, 2.20 GHz
CPU max. support	2	2
Memory	1 x 16GB RDIMM	2 x 16GB RDIMM
Memory max. support	Registered DDR4 ECC memory 24 DIMM Slots Up to 768 GB (24 x RDIMMs)	Registered DDR4 ECC memory 24 DIMM Slots Up to 768 GB (24 x RDIMMs)
Graphics	Integrated 2D video controller / 16 MB DDR3 memory	Integrated 2D video controller / 16 MB DDR3 memory
PCI Slots	•2 x PCIe® 3.0 •1 x I/O module expansion slot •1 x SAS RAID module expansion slot	•2 x PCIe® 3.0 •1 x I/O module expansion slot •1 x SAS RAID module expansion slot
Harddisk	2 x 2TB 2.5" Enterprise SATA 7,200 RPM	2 x 600GB 2.5" SAS 10K RPM
Std. HDD Controller	Intel® ESRT2 SATA RAID 0, 1, 5, 10 (RAID 5 requires key) or Intel® RSTe software SATA RAID 0, 1, 5, 10 (Windows OS support only)	Intel® ESRT2 SATA RAID 0, 1, 5, 10 (RAID 5 requires key) or Intel® RSTe software SATA RAID 0, 1, 5, 10 (Windows OS support only)
H/W RAID Controller	-	H/W RAID 0/1/10/5/50/6/60
Max. # Internal Disks	Up to 8 x 2.5" hot-swappable HDDs	Up to 8 x 2.5" hot-swappable HDDs
LAN controller	Integrated dual-port 10GbE ports	Integrated dual-port 10GbE ports
Redundant Power Supply	Redundant 1100 W 80 PLUS® Platinum-certified AC power supply	Redundant 1100 W 80 PLUS® Platinum-certified AC power supply
Form Factor	1U rack-optimized	1U rack-optimized
Sliding Rail Kit	Free Bundled!!	Free Bundled!!
OS Support	Microsoft® Windows Server® 2016 / 2012 R2 / 2012 Red Hat® Enterprise Linux® 7.1 / 7.2 SUSE® Linux® Enterprise Server 12 SP1 VMware ESXi™ 6.0 / 6.0 Update 1	Microsoft® Windows Server® 2016 / 2012 R2 / 2012 Red Hat® Enterprise Linux® 7.1 / 7.2 SUSE® Linux® Enterprise Server 12 SP1 VMware ESXi™ 6.0 / 6.0 Update 1
Warranty	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand
SRP (inc. VAT)	115,000	147,000

Free bundle Keyboard and Mouse

Free bundle Keyboard and Mouse

Remark

+ **By Order 30 days**

+ Promotion(s) valid within 31 August 2019 or Supplies Last!!!

+ VAT 7% is not included.

+ This promotion cannot be combined with any other promotions or special rates.

+ Acer reserves the right to add, modify, change, or discontinue this promotion and associated products without notice. All products are subject to availability, and all prices are subject to change without notice.

+ Above prices are landed in local currency (THB).

* กรณีต้องการ upgrade สินค้า กรุณาติดต่อเอเซอร์ก่อนการสั่งซื้อทุกครั้ง เอเซอร์ขอสงวนสิทธิ์ในการรับผิดชอบกรณีลูกค้าสั่งซื้อสินค้าเอง หรือ ซื้อสินค้าภายนอก โดยมิได้ได้รับการยืนยัน

* Service by Acer Care เฉพาะกรุงเทพฯ & ปริมณฑล นอกพื้นที่โปรดติดต่อฝ่ายขาย

Rack 2 Way 1U

Rack 2 Way 1U
Altos R360 F8

**Big memory, big storage, uniform
compute and management**



	Altos R380 F4 ACR-USRE7ST004	Altos R380 F4 ACR-USREGST009
CPU Types	1 x Intel® Xeon® Silver 4110 Processor 11M Cache, 2.10 GHz	1 x Intel® Xeon® Gold 5118 Processor 16.5M Cache, 2.30 GHz
CPU max. support	2	2
Memory	1 x 32GB RDIMM	1 x 32GB RDIMM
Memory max. support	Registered DDR4 ECC memory 24 DIMM Slots Up to 768 GB (24 x RDIMMs)	Registered DDR4 ECC memory 24 DIMM Slots Up to 768 GB (24 x RDIMMs)
Graphics	Integrated 2D video controller / 16 MB DDR3 memory	Integrated 2D video controller / 16 MB DDR3 memory
PCI Slots	•8 x PCIe® 3.0 •1 x OCP module expansion slot •1 x RAID module expansion slot	•8 x PCIe® 3.0 •1 x OCP module expansion slot •1 x RAID module expansion slot
Harddisk	2 x 2TB 3.5" Near-line SAS 7,200 RPM	3 x 1.8TB 2.5" SAS 10K RPM
Std. HDD Controller	Intel® ESRT2 SATA RAID 0, 1, 5, 10 (RAID 5 requires key) or Intel® RSTe software SATA RAID 0, 1, 5, 10 (Windows OS support only)	Intel® ESRT2 SATA RAID 0, 1, 5, 10 (RAID 5 requires key) or Intel® RSTe software SATA RAID 0, 1, 5, 10 (Windows OS support only)
H/W RAID Controller	H/W RAID 0/1/10/5/50/6/60	H/W RAID 0/1/10/5/50/6/60
Max. # Internal Disks	Up to 12 x 3.5" hot-swappable HDDs	Up to 24 x 2.5" hot-swappable HDDs
LAN controller	Integrated dual-port 10GbE ports	Integrated dual-port 10GbE ports
Redundant Power Supply	Redundant 1300 W 80 PLUS® Platinum-certified AC power supply	Redundant 1300 W 80 PLUS® Platinum-certified AC power supply
Form Factor	2U rack-optimized	2U rack-optimized
Sliding Rail Kit	Free Bundled!!	Free Bundled!!
OS Support	Microsoft® Windows Server® 2012 R2 SUSE® Linux® Enterprise Server 11 SP3 Red Hat® Enterprise Linux® 6.5 VMware ESXi™ 5.5	Microsoft® Windows Server® 2012 R2 SUSE® Linux® Enterprise Server 11 SP3 Red Hat® Enterprise Linux® 6.5 VMware ESXi™ 5.5
Warranty	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand
SRP (inc. VAT)	153,000	203,000

Free bundle Keyboard and Mouse

Free bundle Keyboard and Mouse

Remark

+ **By Order 30 days**

+ Promotion(s) valid within 31 August 2019 or Supplies Last!!!

+ VAT 7% is not included.

+ This promotion cannot be combined with any other promotions or special rates.

+ Acer reserves the right to add, modify, change, or discontinue this promotion and associated products without notice. All products are subject to availability, and all prices are subject to change without notice.

+ Above prices are landed in local currency (THB).

* กรณีต้องการ upgrade สินค้า กรุณาติดต่อเอเซอร์ก่อนการสั่งซื้อทุกครั้ง เอเซอร์ขอสงวนสิทธิ์ในการรับผิดชอบกรณีลูกค้าสั่งซื้อสินค้าเอง หรือ ซื้อสินค้าภายนอก โดยมีได้ได้รับการยืนยัน

* Service by Acer Care เฉพาะกรุงเทพฯ & ปริมณฑล นอกพื้นที่โปรดติดต่อฝ่ายขาย

DELL PowerEdge : 1 & 2 Socket Rack Server

Part Number	DEL-SNSR4404110	DEL-SNSR4403106	DEL-SNSR4404116	DEL-SNSR5404110
Model	PowerEdge R440	PowerEdge R440	PowerEdge R440	Dell PowerEdge R540
Form Factor	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives + LCD Bezel + 1 x 16x FH Riser	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives + LCD Bezel + 1 x 16x FH Riser	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives + LCD Bezel + 2 x 16x LP Riser	2U, 3.5" Chassis with up to 12 Hot Plug Hard Drives + LCD Bezel + Ready Rails™ Sliding Rails With Cable Management Arm + 1x16 FH, 3xLP PCI Slot
Processor	1 x Intel® Xeon® Silver 4110	1 x Intel® Xeon® Bronze 3106	2 x Intel® Xeon® Silver 4116	1 x Intel® Xeon® Silver 4110
Processor Speed / Core	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W)	1.7G, 8C/8T, 9.6GT/s 2UPI, 11M Cache, No Turbo, No HT (85W)	2.1G, 12C/24T, 9.6GT/s 2UPI, 16.5M Cache, Turbo, HT (85W)	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W) DDR4-2400
Memory	DDR4-2400, 16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank	8GB (1x8GB) RDIMM, 2666MT/s, Dual Rank	32GB (2x16GB) RDIMM, 2666MT/s, Dual Rank	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank
Network	Dual-Port 1GbE On-Board LOM	Dual-Port 1GbE On-Board LOM	Dual-Port 1GbE On-Board LOM	Dual-Port 1GbE On-Board LOM
Harddisk	2 x 1.2TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1TB 7.2K RPM NLSAS 12Gbps 512n 2.5in Hot-plug Hard Drive	4 x 1TB 7.2K RPM NLSAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1.2TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive, 3.5in HYB CARR
RAID Controller	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache
Optical Drive	DVD+/-RW, SATA	DVD+/-RW, SATA	DVD+/-RW, SATA	No Internal Optical Drive for 12 HD Chassis
Power Supply	Dual, Hot-plug, Redundant Power Supply (1+1), 550W	Dual, Hot-plug, Redundant Power Supply (1+1), 550W	Dual, Hot-plug, Redundant Power Supply (1+1), 550W	Dual, Hot-plug, Redundant Power Supply (1+1), 750W
System Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management
Warranty	3Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	133,750	107,000	208,650	139,100

Part Number	DEL-SnSR2401	DEL-SnSR2402	DEL-SnSR3401	DEL-SnSR3402
Model	DEL-SnSR2401	DEL-SnSR2402	Dell PowerEdge R340	Dell PowerEdge R340
Form Factor	3.5" Chassis with up to 4 Hot Plug Hard Drives, 1U/2U 2/4-Post Static Rails	3.5" Chassis with up to 4 Hot Plug Hard Drives, 1U/2U 2/4-Post Static Rails	3.5" Chassis with up to 4 Hot Plug Hard Drives, ReadyRails™ Sliding Rails With Cable Management Arm	3.5" Chassis with up to 4 Hot Plug Hard Drives, ReadyRails™ Sliding Rails With Cable Management Arm
Processor	Intel® Xeon® E-2124	Intel® Xeon® E-2124	Intel® Xeon® E-2124	Intel® Xeon® E-2124
Processor Speed / Core	3.3GHz, 8M cache, 4C/4T, turbo (71W)	3.3GHz, 8M cache, 4C/4T, turbo (71W)	3.3GHz, 8M cache, 4C/4T, turbo (71W)	3.3GHz, 8M cache, 4C/4T, turbo (71W)
Memory	8GB 2666MT/s DDR4 ECC UDIMM	8GB 2666MT/s DDR4 ECC UDIMM	8GB 2666MT/s DDR4 ECC UDIMM	8GB 2666MT/s DDR4 ECC UDIMM
Network	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM
Harddisk	1x BOSS controller card + with 1x M.2 Sticks 240G (No RAID),FH 2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-Plug Hard Drive	2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-Plug Hard Drive	1x BOSS controller card + with 1x M.2 Sticks 240G (No RAID),FH 2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-Plug Hard Drive	2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-Plug Hard Drive
RAID Controller	PERC H330 RAID Controller, Adapter, Full Height	PERC H330 RAID Controller, Adapter, Full Height	PERC H330 RAID Controller, Adapter, Full Height	PERC H330 RAID Controller, Adapter, Full Height
Optical Drive	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal
Power Supply	Single, Cabled Power Supply, 250W	Single, Cabled Power Supply, 250W	Dual, Hot-plug, Redundant Power Supply, 350W	Dual, Hot-plug, Redundant Power Supply, 350W
System Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	67,410	56,710	78,645	70,085

DELL PowerEdge : 2 Socket Rack Server



PowerEdge R640

Part Number	DEL-SNSR6404114	DEL-SNSR6404110	DEL-SNSR7403106
Model	PowerEdge R640	PowerEdge R640	PowerEdge R740
Form Factor	1U, Chassis with up to 10x2.5" Hard Drives, 2x16 LP PCI	1U, Chassis with up to 10x2.5" Hard Drives, 2x16 LP PCI	2U, Chassis with up to 16 x 2.5" Hard Drives, ReadyRail Sliding Rails With Cable Management Arm
Processor	1 x Intel® Xeon® Silver 4110	1 x Intel® Xeon® Silver 4110	1 x Intel® Xeon® Bronze 3104
Processor Speed / Core	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W) DDR4-2400	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W)	1.7G, 6C/6T, 9.6GT/s 2UPI, 8M Cache, No Turbo, No HT (85W)
Memory	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank	DDR4-2400	DDR4-2133
Network	Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC
Harddisk	2 x 600GB 15K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1.2TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 900GB 15K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive
RAID Controller	PERC H740P RAID Controller, 8Gb NV Cache, Minicard	PERC H730P RAID Controller, 2Gb NV Cache, Minicard	PERC H740P RAID Controller, 8Gb NV Cache, Minicard
Optical Drive	No Optical Drive	No Optical Drive	DVD+/-RW,SATA,Internal
Power Supply	Dual, Hot-plug, Redundant Power Supply (1+1), 750W	Dual, Hot-plug, Redundant Power Supply (1+1), 750W	Dual, Hot-plug, Redundant Power Supply (1+1), 750W
System Management	iDRAC9 Enterprise with OME Server Configuration Management, 2x 32GB microSDHC/SDXC Card	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management, 2x 32GB microSDHC/SDXC Card
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport and Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	167,883	144,450	141,133



PowerEdge R740

Part Number	DEL-SNSR7404112	DEL-SNSR7404110	DEL-SNSR7404114
Model	PowerEdge R740	PowerEdge R740	PowerEdge R740
Form Factor	2U, Chassis with up to 16 x 2.5" Hard Drives, ReadyRail Sliding Rails With Cable Management Arm	2U, Chassis with up to 16 x 2.5" Hard Drives + LCD Bezel, ReadyRail Sliding Rails With Cable Management Arm	2U, Chassis with up to 16 x 2.5" Hard Drives + LCD Bezel, ReadyRail Sliding Rails With Cable Management Arm
Processor	1 x Intel® Xeon® Silver 4112	1 x Intel® Xeon® Silver 4110	1 x Intel® Xeon® Silver 4114
Processor Speed / Core	2.6G, 4C/8T, 9.6GT/s 2UPI, 8.25M Cache, Turbo, HT (85W) DDR4-2400	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W) DDR4-2400	2.2G, 10C/20T, 9.6GT/s 2UPI, 14M Cache, Turbo, HT (85W)
Memory	32GB (2x16GB) RDIMM, 2666MT/s, Dual Rank	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank
Network	Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC	Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC	Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC
Harddisk	2 x 1.8TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1.2TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1.8TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive
RAID Controller	PERC H740P RAID Controller, 8Gb NV Cache, Minicard	PERC H730P RAID Controller, 2Gb NV Cache, Minicard	PERC H730P RAID Controller, 2Gb NV Cache, Minicard
Optical Drive	DVD+/-RW,SATA,Internal	DVD+/-RW,SATA,Internal	DVD+/-RW,SATA,Internal
Power Supply	Dual, Hot-plug, Redundant Power Supply (1+1), 750W	Dual, Hot-plug, Redundant Power Supply (1+1), 1100W	Dual, Hot-plug, Redundant Power Supply (1+1), 1100W
System Management	iDRAC9 Enterprise with OME Server Configuration Management, 2x 32GB microSDHC/SDXC Card	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management
Warranty	3Yr ProSupport and Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport and Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport and Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	181,900	146,590	165,850

2 CPU Rack Server



	System X3550 M5 LNV-8869PET	System X3550 M5 LNV-8869PEP	System X3550 M5 LNV-8869PER	System X3650 M5 LNV-8871PFH
P/N				
CPU Types	Xeon 6C E5-2603v4 85W 1.7GHz	Xeon 8C E5-2620v4 85W 2.1GHz	Xeon 10C E5-2630v4 85W 2.2GHz	Xeon E5-2609v4 85W 1.7GHz
CPU Min., max	1, option to 2	1, option to 2	1, option to 2	1, option to 2
CPU L3 Cache	15MB	20MB	25MB	20MB
ECC Memory	1x8GB 1866MHz	1x16GB 2133Hz	1x16GB 2133Hz	1x8GB 1866MHz
Graphic	Matrox G200eR2 with 16 MB memory integrated into the IMM2.1. Maximum resolution is 1600x1200 at 75 Hz with 16 M colors.	Matrox G200eR2 with 16 MB memory integrated into the IMM2.1. Maximum resolution is 1600x1200 at 75 Hz with 16 M colors.	Matrox G200eR2 with 16 MB memory integrated into the IMM2.1. Maximum resolution is 1600x1200 at 75 Hz with 16 M colors.	Matrox G200eR2 with 16 MB of memory integrated into the IMM2. Maximum resolution is 1600x1200 at 75 Hz with 16 M colors
Bus Type				
PCI Slot	Three PCIe 3.0 slots Up to nine slots	Three PCIe 3.0 slots Up to nine slots	Three PCIe 3.0 slots Up to nine slots	Three PCIe 3.0 slots Up to nine slots
Harddisk	Hot Swap SAS / Sata	Hot Swap SAS / Sata	Hot Swap SAS / Sata	Hot Swap SAS / Sata
Onboard RAID	SR M1215 (Raid 0 , 1 , 10)	SR M5210 (Raid 0 , 1 , 10 , 5 , 50)	SR M5210 (Raid 0 , 1 , 10 , 5 , 50)	SR M1215 (Raid 0 , 1 , 10)
Optical Drive	Option DVD-ROM or Multiburner.	Option DVD-ROM or Multiburner.	Option DVD-ROM or Multiburner.	Option DVD-ROM or Multiburner.
Diskette	USB Only	USB Only	USB Only	USB Only
Total, Hotswap	4x 2.5" HS	4x 2.5" HS	4x 2.5" HS	8x 2.5" HS / 16
Max, Internal disks				
Interfaces	Front : 4x 3.5" and 10x 2.5" drive bay models: 3x USB 2.0 and 1x DB-15 video ports. 8x 2.5" drive bay models: 1x USB 2.0 (standard); or 2x USB 2.0 and 1x DB-15 video ports (optional). Rear: 2x USB 3.0, 1x DB-15 video, 1x RJ-45 systems management, 4x RJ-45 GbE network ports. Optional 1x DB-9 serial port. Internal: 1x USB 2.0 port (for embedded hypervisor), 1x SD Media Adapter slot (for embedded hypervisor)	Front : 4x 3.5" and 10x 2.5" drive bay models: 3x USB 2.0 and 1x DB-15 video ports. 8x 2.5" drive bay models: 1x USB 2.0 (standard); or 2x USB 2.0 and 1x DB-15 video ports (optional). Rear: 2x USB 3.0, 1x DB-15 video, 1x RJ-45 systems management, 4x RJ-45 GbE network ports. Optional 1x DB-9 serial port. Internal: 1x USB 2.0 port (for embedded hypervisor), 1x SD Media Adapter slot (for embedded hypervisor)	Front : 4x 3.5" and 10x 2.5" drive bay models: 3x USB 2.0 and 1x DB-15 video ports. 8x 2.5" drive bay models: 1x USB 2.0 (standard); or 2x USB 2.0 and 1x DB-15 video ports (optional). Rear: 2x USB 3.0, 1x DB-15 video, 1x RJ-45 systems management, 4x RJ-45 GbE network ports. Optional 1x DB-9 serial port. Internal: 1x USB 2.0 port (for embedded hypervisor), 1x SD Media Adapter slot (for embedded hypervisor)	Front : 4x 3.5" and 10x 2.5" drive bay models: 3x USB 2.0 and 1x DB-15 video ports. 8x 2.5" drive bay models: 1x USB 2.0 (standard); or 2x USB 2.0 and 1x DB-15 video ports (optional). Rear: 2x USB 3.0, 1x DB-15 video, 1x RJ-45 systems management, 4x RJ-45 GbE network ports. Optional 1x DB-9 serial port. Internal: 1x USB 2.0 port (for embedded hypervisor), 1x SD Media Adapter slot (for embedded hypervisor)
Onboard Gigabit Ethernet, Redundant Power	Four integrated RJ-45 Gigabit Ethernet 1000BASE-T ports (BCM5719); optional Mezzanine LOM (ML2) slot for dual-port or quad-port 10 GbE cards with SFP+ or RJ-45 connectors or quad-port GbE cards with RJ-45 connectors.	Four integrated RJ-45 Gigabit Ethernet 1000BASE-T ports (BCM5719); optional Mezzanine LOM (ML2) slot for dual-port or quad-port 10 GbE cards with SFP+ or RJ-45 connectors or quad-port GbE cards with RJ-45 connectors.	Four integrated RJ-45 Gigabit Ethernet 1000BASE-T ports (BCM5719); optional Mezzanine LOM (ML2) slot for dual-port or quad-port 10 GbE cards with SFP+ or RJ-45 connectors or quad-port GbE cards with RJ-45 connectors.	Four integrated RJ-45 Gigabit Ethernet 1000BASE-T ports (BCM5719); optional Mezzanine LOM (ML2) slot for dual-port or quad-port 10 GbE cards with SFP+ or RJ-45 connectors or quad-port GbE cards with RJ-45 connectors.
Dimensions (units)	Width: 42.9 cm, Depth: 73.4 cm, Height: 4.3 cm	Width: 42.9 cm, Depth: 73.4 cm, Height: 4.3 cm	Width: 42.9 cm, Depth: 73.4 cm, Height: 4.3 cm	Width: 42.9 cm, Depth: 73.4 cm, Height: 4.3 cm
Mechanical	1U rack	1U rack	1U rack	1U rack
Power Supply	Two redundant hot-swap 750 Watts p/s	Two redundant hot-swap 750 Watts p/s	Two redundant hot-swap 750 Watts p/s	Two redundant hot-swap 750 Watts p/s
OS Support	Microsoft Windows Server 2012 R2 and 2012; Red Hat Enterprise Linux 7 SUSE Linux Enterprise Server 11 and 12; VMware vSphere (ESXi) 5.5 and 6.0.	Microsoft Windows Server 2012 R2 and 2012; Red Hat Enterprise Linux 7 SUSE Linux Enterprise Server 11 and 12; VMware vSphere (ESXi) 5.5 and 6.0.	Microsoft Windows Server 2012 R2 and 2012; Red Hat Enterprise Linux 7 SUSE Linux Enterprise Server 11 and 12; VMware vSphere (ESXi) 5.5 and 6.0.	Microsoft Windows Server 2012 R2 and 2012; Red Hat Enterprise Linux 7 SUSE Linux Enterprise Server 11 and 12; VMware vSphere (ESXi) 5.5 and 6.0.
Warranty	3 year on-site 24x7x4	3 year on-site 24x7x4	3 year on-site 24x7x4	3 year on-site 24x7x4
SRP (Inc. VAT)	77,896	92,020	103,255	85,386

หมายเหตุ : กรณีต้องการใช้ Linux หรือ Netware ต้องตรวจสอบ Version ที่ IBM สามารถ Support ได้จาก <http://www.pc.ibm.com/US/compat/indexsp.html>

1 & 2 CPU Rack Server



Thinksystem SR530



Thinksystem SR630



System X3550 M5

System X3550 M5

P/N	LNV-7X08S4VA00	LNV-7X02S4UX00	LNV-8869PEG	LNV-8869PEF
CPU Types	1x 4110 8C 85W 2.1GHz	1x 5115 10C 85W 2.4GHz	Xeon 8C E5-2620v4 85W 2.1GHz	2xXeon 10C E5-2640v4 90W 2.4GHz
CPU Min., max	1, option to 2	1, option to 2	1, option to 2	2
CPU L2 / L3 Cache	11MB / -	13.75MB / -	- / 20MB	- / 25MB
ECC Memory	1x 16GB TruDDR4 2666 MHz (1Rx4 1.2V) RDIMM	1x 16GB TruDDR4 2666 MHz (2Rx8 1.2V) RDIMM	1x16GB 2133Hz	2x16GB 2133Hz
Graphic	Matrox G200 with 16 MB memory integrated into the XClarity Controller. Maximum resolution is 1920x1200 at 60 Hz with 16 bits per pixel.	Matrox G200 with 16 MB memory integrated into the XClarity Controller. Maximum resolution is 1920x1200 at 60 Hz with 16 bits per pixel.	Matrox G200eR2 with 16 MB memory integrated into the IMM2.1. Maximum resolution is 1600x1200 at 75 Hz with 16 M colors.	Matrox G200eR2 with 16 MB memory integrated into the IMM2.1. Maximum resolution is 1600x1200 at 75 Hz with 16 M colors.
Bus Type	2666MHz	2666MHz		
PCI Slot	Up to three slots depending on the riser cards installed. The slots are as follows: Slot 1: PCIe 3.0 x8; low profile Slot 2: PCIe 3.0 x16 or ML2 x8; low profile or full-height, half-length Slot 3: PCIe 3.0 x8 or x16; low profile PCIe x16 slot 3 requires the second processor to be installed.	Up to four slots. Slot 4 is the fixed slot on the system planar, and the remaining slots depend on the riser cards installed. The slots are as follows: Slot 1: PCIe 3.0 x8, ML2 x8, or ML2 x16; low profile Slot 2: PCIe 3.0 x16 or x8; low profile or full-height, half-length Slot 3: PCIe 3.0 x16; low profile Slot 4: PCIe 3.0 x8 (dedicated to an internal storage controller) Slot 3 requires the second processor to be installed.	Three PCIe 3.0 slots Up to nine slots	Three PCIe 3.0 slots Up to nine slots
Harddisk	Hot Swap SAS / SATA	Hot Swap SAS / SATA	Hot Swap SAS / SATA 2x300GB HS 2.5" SAS	Hot Swap SAS / SATA 4x600GB HS 2.5" SAS
Onboard RAID	RAID 930-8i 2GB Flash PCIe 12Gb Adapter	RAID 930-8i 2GB Flash PCIe 12Gb Adapter	SR M1215 (Raid 0 , 1 , 10 , 5 , 50)	SR M1215 (Raid 0 , 1 , 10 , 5 , 50)
Optical Drive			Option DVD-ROM or Multiburner.	Option DVD-ROM or Multiburner.
Diskette			USB Only	USB Only
Total, Hotswap	8/8 HS SFF	8/8 SFF	4x 2.5" HS	4x 2.5" HS
Max, Internal disks				
Interfaces	Front: 1x USB 2.0 port with XClarity Controller access. 1x USB 3.0 port. 1x DB-15 VGA port (optional). Rear: 2x USB 3.0 ports and 1x DB-15 VGA port. Optional 1x DB-9 serial port	Front: 1x USB 2.0 port with XClarity Controller access. 1x USB 3.0 port. 1x DB-15 VGA port (optional). Rear: 2x USB 3.0 ports and 1x DB-15 VGA port. Optional 1x DB-9 serial port.	Front : 4x 3.5" and 10x 2.5" drive bay models: 3x USB 2.0 and 1x DB-15 video ports. 8x 2.5" drive bay models: 1x USB 2.0 (standard); or 2x USB 2.0 and 1x DB-15 video ports (optional). Rear: 2x USB 3.0, 1x DB-15 video, 1x RJ-45 systems management, 4x RJ-45 GbE network ports. Optional 1x DB-9 serial port. Internal: 1x USB 2.0 port (for embedded hypervisor), 1x SD Media Adapter slot (for embedded hypervisor)	Front : 4x 3.5" and 10x 2.5" drive bay models: 3x USB 2.0 and 1x DB-15 video ports. 8x 2.5" drive bay models: 1x USB 2.0 (standard); or 2x USB 2.0 and 1x DB-15 video ports (optional). Rear: 2x USB 3.0, 1x DB-15 video, 1x RJ-45 systems management, 4x RJ-45 GbE network ports. Optional 1x DB-9 serial port. Internal: 1x USB 2.0 port (for embedded hypervisor), 1x SD Media Adapter slot (for embedded hypervisor)
Onboard Gigabit Ethernet, Redundant Power	2x Integrated 1 GbE RJ-45 ports (no 10/100 Mb support) Onboard LOM slot for up to 4x 1/10 Gb Ethernet ports: 2x 1 GbE RJ-45 ports (no 10/100 Mb support) 2x 10 GbE RJ-45 ports (no 10/100 Mb support) 2x 10 GbE SFP+ ports (no 10/100 Mb support) Optional Mezzanine LOM (ML2) slot for dual-port 10 GbE cards with SFP+ or RJ-45 connectors. 1x RJ-45 10/100/1000 Mb Ethernet systems management port.	Onboard LOM slot for up to 4x 1/10 Gb Ethernet ports: 2x or 4x 1 GbE RJ-45 ports (no 10/100 Mb support) 2x or 4x 10 GbE RJ-45 ports (no 10/100 Mb support) 2x or 4x 10 GbE SFP+ ports (no 10/100 Mb support) Optional Mezzanine LOM (ML2) slot for dual-port 10 GbE cards with SFP+ or RJ-45 connectors or single- or dual-port 25 GbE cards with SFP28 connectors. 1x RJ-45 10/100/1000 Mb Ethernet systems management port.	Four integrated RJ-45 Gigabit Ethernet 1000BASE-T ports (BCM5719); optional Mezzanine LOM (ML2) slot for dual-port or quad-port 10 GbE cards with SFP+ or RJ-45 connectors or quad-port GbE cards with RJ-45 connectors.	Four integrated RJ-45 Gigabit Ethernet 1000BASE-T ports (BCM5719); optional Mezzanine LOM (ML2) slot for dual-port or quad-port 10 GbE cards with SFP+ or RJ-45 connectors or quad-port GbE cards with RJ-45 connectors.
Dimensions (units)	Height: 43 mm (1.7 in), width: 434 mm (17.1 in), depth: 715 mm (28.1 in)	Height: 43 mm (1.7 in), width: 434 mm (17.1 in), depth: 715 mm (28.1 in)	Width: 42.9 cm, Depth: 73.4 cm, Height: 4.3 cm	Width: 42.9 cm, Depth: 73.4 cm, Height: 4.3 cm
Mechanical	1U rack-mount	1U rack-mount.	1U rack	1U rack
Power Supply	2x 750W (230/115V) Platinum HS	2x 750W (230/115V) Platinum HS	Two redundant hot-swap 750 Watts p/s	Two redundant hot-swap 750 Watts p/s
OS Support	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware, ESXi.	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware, ESXi.	Microsoft Windows Server 2012 R2 and 2012; Red Hat Enterprise Linux 7, SUSE Linux Enterprise Server 11 and 12; VMware vSphere (ESXi) 5.5 and 6.0.	Microsoft Windows Server 2012 R2 and 2012; Red Hat Enterprise Linux 7, SUSE Linux Enterprise Server 11 and 12; VMware vSphere (ESXi) 5.5 and 6.0.
Warranty	3 year on-site 24x7x4	3 year on-site 24x7x4	3 year on-site 24x7x4	3 year on-site 24x7x4
SRP (inc. VAT)	104,646	157,718	99,724	193,349

หมายเหตุ : กรณีต้องการใช้ Linux หรือ Netware ต้องตรวจสอบ Version ที่ IBM สามารถ Support ได้จาก <http://www.pc.ibm.com/US/compat/indexsp.html>

2 CPU Rack Server



Thinksystem SR550

Thinksystem SR550

System X3650 M5

System X3650 M5

P/N	LNV-7X04S4VD00	LNV-7X04S4V300	LNV-8871PFE	LNV-8871PFF
CPU Types	1x 4110 8C 85W 2.1GHz	1x 4114 10C 85W 2.2GHz	Xeon 8C E5-2620 v4 85W 2.1GHz	2xXeon 10C E5-2640 v4 90W 2.4GHz
CPU Min., max	1, option to 2	1, option to 2	1, option to 2	2
CPU L2 / L3 Cache	11MB / -	13.75MB	20MB	25MB
ECC Memory	1x 16GB TruDDR4 2666 MHz (1Rx4 1.2V) RDIMM	1x 16GB TruDDR4 2666 MHz (1Rx4 1.2V) RDIMM	1x16GB 2133Hz	2x16GB 2133Hz
Graphic	G200 graphics with 16 MB memory with 2D hardware accelerator, integrated into the XClarity Controller. Maximum resolution is 1920x1200 32bpp at 60Hz.	G200 graphics with 16 MB memory with 2D hardware accelerator, integrated into the XClarity Controller. Maximum resolution is 1920x1200 32bpp at 60Hz.	Matrox G200eR2 with 16 MB of memory integrated into the IMM2. Maximum resolution is 1600x1200 at 75 Hz with 16 M colors	Matrox G200eR2 with 16 MB of memory integrated into the IMM2. Maximum resolution is 1600x1200 at 75 Hz with 16 M colors
Bus Type	2666MHz	2666MHz		
PCI Slot	Up to six slots. Slot 4 is the fixed slots on the system planar, and the remaining slots depend on the riser cards installed. The slots are as follows: Slot 1: PCIe 3.0 x16 or PCIe 3.0 x8; full-height, half-length (PCIe x16 slot is double-wide) Slot 2: PCIe 3.0 x8; full-height, half-length (not present if the slot 1 is PCIe x16) Slot 3: PCIe 3.0 x8 or ML2 x8; full-height, half-length Slot 4: PCIe 3.0 x8; low profile (vertical slot on system planar) Slot 5: PCIe 3.0 x16; full-height, half-length Slot 6: PCIe 3.0 x8; full-height, half-length Slot 5 requires the second processor to be installed.	Up to six slots. Slot 4 is the fixed slots on the system planar, and the remaining slots depend on the riser cards installed. The slots are as follows: Slot 1: PCIe 3.0 x16 or PCIe 3.0 x8; full-height, half-length (PCIe x16 slot is double-wide) Slot 2: PCIe 3.0 x8; full-height, half-length (not present if the slot 1 is PCIe x16) Slot 3: PCIe 3.0 x8 or ML2 x8; full-height, half-length Slot 4: PCIe 3.0 x8; low profile (vertical slot on system planar) Slot 5: PCIe 3.0 x16; full-height, half-length Slot 6: PCIe 3.0 x8; full-height, half-length Slot 5 requires the second processor to be installed.	Three PCIe 3.0 slots Up to nine slots	Three PCIe 3.0 slots Up to nine slots
Harddisk	Hot Swap SAS / SATA	Hot Swap SAS / SATA	Hot Swap SAS / SATA 2x300GB HS 2.5" SAS	Hot Swap SAS / SATA 4x600GB HS 2.5" SAS
Onboard RAID	RAID 930-8i 2GB Flash PCIe 12Gb Adapter	RAID 930-8i 2GB Flash PCIe 12Gb Adapter	SR M1215 (Raid 0 , 1 , 10 , 5 , 50)	SR M1215 (Raid 0 , 1 , 10 , 5 , 50)
Optical Drive			Option DVD-ROM or Multiburner.	Option DVD-ROM or Multiburner.
Diskette			USB Only	USB Only
Total, Hotswap	8/16 HS SFF	8/16 HS SFF	8x 2.5" HS / 16	8x 2.5" HS / 16
Max, Internal disks				
Interfaces	Front: 1x USB 2.0 port with XClarity Controller access. 1x USB 3.0 port. 1x DB-15 VGA port (optional). Rear: 2x USB 3.0 ports and 1x DB-15 VGA port. Optional 1x DB-9 serial port.	Front: 1x USB 2.0 port with XClarity Controller access. 1x USB 3.0 port. 1x DB-15 VGA port (optional). Rear: 2x USB 3.0 ports and 1x DB-15 VGA port. Optional 1x DB-9 serial port.	Front : 4x 3.5" and 10x 2.5" drive bay models: 3x USB 2.0 and 1x DB-15 video ports. 8x 2.5" drive bay models: 1x USB 2.0 (standard); or 2x USB 2.0 and 1x DB-15 video ports (optional). Rear: 2x USB 3.0, 1x DB-15 video, 1x RJ-45 systems management, 4x RJ-45 GbE network ports. Optional 1x DB-9 serial port. Internal: 1x USB 2.0 port (for embedded hypervisor), 1x SD Media Adapter slot (for embedded hypervisor)	Front : 4x 3.5" and 10x 2.5" drive bay models: 3x USB 2.0 and 1x DB-15 video ports. 8x 2.5" drive bay models: 1x USB 2.0 (standard); or 2x USB 2.0 and 1x DB-15 video ports (optional). Rear: 2x USB 3.0, 1x DB-15 video, 1x RJ-45 systems management, 4x RJ-45 GbE network ports. Optional 1x DB-9 serial port. Internal: 1x USB 2.0 port (for embedded hypervisor), 1x SD Media Adapter slot (for embedded hypervisor)
Onboard Gigabit Ethernet, Redundant Power	2x Integrated 1 GbE RJ-45 ports (no 10/100 Mb support) Onboard LOM slot for two additional 2x 1/10 Gb Ethernet ports: 2x 1 GbE RJ-45 ports (no 10/100 Mb support) 2x 10 GbE RJ-45 ports (no 10/100 Mb support) 2x 10 GbE SFP+ ports (no 10/100 Mb support) Optional Mezzanine LOM (ML2) slot for dual-port 10 GbE cards with SFP+ or RJ-45 connectors. 1x RJ-45 10/100/1000 Mb Ethernet systems management port.	2x Integrated 1 GbE RJ-45 ports (no 10/100 Mb support) Onboard LOM slot for two additional 2x 1/10 Gb Ethernet ports: 2x 1 GbE RJ-45 ports (no 10/100 Mb support) 2x 10 GbE RJ-45 ports (no 10/100 Mb support) 2x 10 GbE SFP+ ports (no 10/100 Mb support) Optional Mezzanine LOM (ML2) slot for dual-port 10 GbE cards with SFP+ or RJ-45 connectors. 1x RJ-45 10/100/1000 Mb Ethernet systems management port.	Four integrated RJ-45 Gigabit Ethernet 1000BASE-T ports (BCM5719); optional Mezzanine LOM (ML2) slot for dual-port or quad-port 10 GbE cards with SFP+ or RJ-45 connectors or quad-port GbE cards with RJ-45 connectors.	Four integrated RJ-45 Gigabit Ethernet 1000BASE-T ports (BCM5719); optional Mezzanine LOM (ML2) slot for dual-port or quad-port 10 GbE cards with SFP+ or RJ-45 connectors or quad-port GbE cards with RJ-45 connectors.
Dimensions (units)	Height: 87 mm (3.4 in), width: 445 mm (17.5 in), depth: 720 mm (28.3 in)	Height: 87 mm (3.4 in), width: 445 mm (17.5 in), depth: 720 mm (28.3 in)	Width: 42.9 cm, Depth: 73.4 cm, Height: 4.3 cm	Width: 42.9 cm, Depth: 73.4 cm, Height: 4.3 cm
Mechanical	2U rack-mount	2U rack-mount	1U rack	1U rack
Power Supply	2x 750W (230/115V) Platinum HS	2x 750W (230/115V) Platinum HS	Two redundant hot-swap 750 Watts p/s	Two redundant hot-swap 750 Watts p/s
OS Support	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware, ESXi.	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware, ESXi.	Microsoft Windows Server 2012 R2 and 2012; Red Hat Enterprise Linux 7,SUSE Linux Enterprise Server 11 and 12; VMware vSphere (ESXi) 5.5 and 6.0.	Microsoft Windows Server 2012 R2 and 2012; Red Hat Enterprise Linux 7,SUSE Linux Enterprise Server 11 and 12; VMware vSphere (ESXi) 5.5 and 6.0.
Warranty	3 year on-site 24x7x4	3 year on-site 24x7x4	3 year on-site 24x7x4	3 year on-site 24x7x4
SRP (inc. VAT)	107,214	117,486	103,576	205,868

หมายเหตุ : กรณีต้องการใช้ Linux หรือ Netware ต้องตรวจสอบ Version ที่ IBM สามารถ Support ได้จาก <http://www.pc.ibm.com/US/compat/indexsp.html>

Rack 2 CPU 1U & 2U



Server HP มี Onsite Service ทุกระดับ
 สอบถามรายละเอียดโทร. 02-118-6300

HPE ProLiant DL325 Gen10
 HPE-P04647-B21

HPE ProLiant DL360 Gen10
 HPE-867962-B21

HPE ProLiant DL385 Gen10
 HPE-878724-B21

HPE ProLiant DL380 Gen10
 HPE-826565-B21

CPU Types	AMD EPYC 7351 (2.4GHz/16-core/155-170W) Processor	Intel® Xeon® Silver 4114 (2.2GHz/10-core/13.75MB/85W) Processor	2x AMD EPYC 7451 (2.3GHz/24-core/180W) Processor	Intel® Xeon® 4114 (2.2GHz/10-core/13.75MB/85W) Processor
CPU Min., max	1	1, option to 2	Two processors	1, option to 2
CPU L3 Cache	64 MB	13.75 MB	64 MB	13.75 MB
ECC Memory	16GB (2x8GB) DDR4-2666 Registered Smart Memory	HPE 16GB (1x16GB) Dual Rank x8 DDR4-2666 Registered Smart Memory Kit	64 GB RDIMM DR 2666 MT/s (2x 32 GB)	32 GB RDIMM 2R 2666 MT/s (2x 16 GB)
Graphic	Integrated Video Standard		Integrated Video Standard	Integrated Video Standard
PCI Slot	2-slots (x16, x8) as standard	2 PCIe: 1 x16 FH / 1 x8 LP	3-slots (x8, x16, x8) as standard,	3-slots (x8, x16, x8) as standard
Harddisk	8 SFF Chassis	8SFF	8 SFF Chassis	8 SFF HDD Bays
Onboard RAID	E208i-a	P408i-a/2GB	P408i-a w/Expander	HPE Smart Array P408i-a SR (2GB Cache) Controller (RAID 0, 1, 5, 6, 10, 50, 60, 1 ADM, 10 ADM)
Optical Drive	Optional: DVD-ROM, DVD-RW	Optional: DVD-ROM, DVD-RW	DVD-RW	Optional: DVD-ROM, DVD-RW
Total, Hotswap	8 SFF HDD Bays	8SFF	8 SFF Chassis	8 SFF HDD Bays
Max, Internal disks	8 SFF Chassis		8 SFF Chassis	
Interfaces	1 Rear VGA Port - Standard	Video 1 USB 5		Video1 (rear), Network RJ-45 (Ethernet) USB 5
Onboard Gigabit Ethernet, Redundant Power	HPE 1Gb Ethernet 4-Port 331i Adapter plus	Embedded 4-port 1GbE	HPE 1Gb Ethernet 4-Port 331i Adapter plus	HPE 1Gb Ethernet 4-Port 331i Adapter plus
Dimensions (units)	(Height 4.29 x Width 43.46 x Depth 61.49 cm)	(Height 4.29 x Width 43.46 x Depth 70.7 cm)	(Height 8.73 x Width 44.55 x Depth 67.94 cm)	(Height 8.73 x Width 44.54 x Depth 67.94 cm)
Mechanical	rack 1U	rack 1U	rack 2U	rack 2U
Power Supply	HPE 500W Flex Slot Platinum Power Supply	HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	2x 800W HPE FlexSlot power supply	1) HPE 500W Flex Slot Platinum Power Supply
OS Support	Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)	Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)	Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)	Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)
Warranty	3-year parts, 3-year labor, 3-year onsite support with next business day response 3/3/3	3-year parts, 3-year labor, 3-year onsite support with next business day response. 3/3/3	3-year parts, 3-year labor, 3-year onsite support with next business day response 3/3/3	3-year parts, 3-year labor, 3-year onsite support with next business day response. 3/3/3
SRP (inc. VAT)	129,470	121,200	332,600	129,700
	HPE-872479-B21 HPE 1.2TB X 2 UNIT	HPE-872477-B21 HPE 600GB SAS 12G Enterprise 10K SFF X 2	HPE-872479-B21 HPE 1.2TB X 2 UNIT	HPE-872479-B21 HPE 1.2TB



	HPE ProLiant DL360 Gen10 CLX P03630-B21	HPE ProLiant DL380 Gen10 CLX P02462-B21
Processor type	Silver 4208 2.1GHz 8-core 1P	Silver 4208 2.1GHz 8-core 1P
CPU Min.,Max	sausu Two processors	sausu Two processors
CPU L3 Cache	11 MB	11 MB
ECC Memory	16 GB RDIMM 2R 2933 MT/s(1x 16 GB)	16 GB RDIMM 2R 2933 MT/s(1x 16 GB)
Graphic	Integrated Video Standard	Integrated Video Standard
PCI Slot	2 PCIe: 1 x16 FH, 1 x8 LP	3-slots (x8, x16, x8 with dual m.2)
Hard Drives	8 SFF Chassis	8 SFF Chassis
Onboard Raid	P408i-a/2GB with Smart Storage Battery	P408i-a w/2GB cache
Optical drive	Not included (Optical Drive options available)	Not included (Optical Drive options available)
Total Hotswap	8 SFF HDD Bays	8 SFF Chassis
Max. # Internal Disks	8 SFF Chassis	8 SFF Chassis
Interface	1 Rear VGA Port - Standard	1 Rear VGA Port - Standard
Onboard Gigabit Ethernet	HPE 1Gb Ethernet 4-Port 331i Adapter plus	HPE 1Gb Ethernet 4-Port 331i Adapter plus
Dimension	(Height 4.29 x Width 43.46 x Depth 70.7 cm)	(Height 8.73 x Width 44.55 x Depth 67.94 cm)
Mechanical	1U rack	2U rack
Power Supply	1) HPE 500W Flex Slot Platinum Power Supply	1x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit
OS Support	Microsoft Windows Server	*Microsoft Windows Server
Warranty	Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)	Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)*
Standard Warranty	3-year parts, 3-year labor, 3-year onsite support with next business day response 3/3/3	3-year parts, 3-year labor, 3-year onsite support with next business day response 3/3/3
SRP (inc. VAT)	141,454	145,306
	P09712-B21 HPE 480GB SATA MU SFF SC DS SSD X 3 UNIT	P09712-B21 HPE 480GB SATA MU SFF SC DS SSD X 3 UNIT