

Rack 2 Way 1U

Rack 1U; Altos R360F4

Rack 2U; Altos R380F4

**High performance,
small footprint.**



	Altos R369 F4 ACR-USRMUST001	Altos R389 F4 ACR-USRNDST002
CPU Types	1x Intel® Xeon® Silver 4208 Processor 11M Cache, 2.10 GHz (8-core)	1 x Intel® Xeon® Silver 4214 Processor 16.5M Cache, 2.20 GHz (12-core)
CPU max. support	2	2
Memory	16GB (1x16GB)	32GB (2x16GB)
Memory max. support	Registered DDR4 ECC memory 24 DIMM Slots Up to 24 x DIMMs	Registered DDR4 ECC memory 24 DIMM Slots Up to 24 x DIMMs
Graphics	ASPEED AST2500 BMC	ASPEED AST2500 BMC
PCI Slots	2x PCIe x8 slot (Gen3 x8), Low profile half-length 1x PCIe x16 slots (Gen3 x16), Low profile half-length 2x OCP mezzanine slots (PCIe Gen3 x 16)	2 x PCIe x16 slots (Gen3 x16 or x8) 2 x PCIe x8 slots (Gen3 x0 or x8) 2 x PCIe x8 slots (Gen3 x8) 1 x PCIe x8 slot (Gen3 x0 or x8) 1 x PCIe x16 slot (Gen3 x16 or x8) 2 x OCP mezzanine slots2 (PCIe Gen3 x 16)
Harddisk	2 x 1TB 3.5" Enterprise SATA 7,200 RPM	2 x 600GB 2.5" 10K RPM SAS HDD
Std. HDD Controller	Integrated SATA RAID 0, 1, 5, 10 (Windows OS support only)	Integrated SATA RAID 0, 1, 5, 10 (Windows OS support only)
H/W RAID Controller	-	H/W RAID 0/1/10/5/50
Max. # Internal Disks supports	Up to 4 x 3.5" (2.5" optional) hot-swappable HDDs	4 x 2.5" U.2 + 20 x 2.5" SAS/SATA hot-swappable bays for HDD/SSD
LAN controller	Integrated Dual 1GbE LAN ports with Intel® I350-AM2	Dual 1GbE LAN ports with Intel® I350-AM2
Redundant Power Supply	Redundant 800W redundant power supply, 80 PLUS Platinum	Redundant 800W redundant power supply, 80 PLUS Platinum
Form Factor	1U rack-optimized	2U rack-optimized
Sliding Rail Kit	Free Bundled!!	Free Bundled!!
OS Support (Not Provide OS)	Window Server 2019, 2016 Red Hat® Enterprise Linux® 7.x and 8.0 VMware ESXI 6.7 Update 3	Window Server 2019, 2016 Red Hat® Enterprise Linux® 7.x and 8.0 VMware ESXI 6.7 Update 3
Warranty	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand
SRP (inc. VAT)	102,506	173,019

Free bundle Keyboard and Mouse

Free bundle Keyboard and Mouse

Remark

- + By Order 45-60 days
- + Promotion(s) valid within July 1 - July 31, 2020 or Supplies Last!!!
- + VAT 7% is not included.
- + This promotion cannot be combined with any other promotions or special rates.
- + Acer reserves the right to add, modify, change, or discontinue this promotion and associated products without notice. All products are subject to availability, and all prices are subject to change without notice.
- + Above prices are landed in local currency (THB).

* กรณีต้องการ upgrade สินค้า กรุณาติดต่อเอเซอร์ก่อนการสั่งซื้อทุกครั้ง เอเซอร์ของสงวนสิทธิ์ในการรับผิดชอบกรณีลูกค้าสั่งซื้อสินค้าเอง หรือ ซื้อสินค้าภายนอก โดยมิได้รับการยืนยัน

* Service by Acer Care เฉพาะกรุงเทพ & ปริมณฑล นอกพื้นที่โปรดติดต่อฝ่ายขาย

DELL PowerEdge : 1 & 2 Socket Rack Server

Part Number	DEL-SNSR4404110	DEL-SNSR4403106	DEL-SNSR4404116	DEL-SNSR5404110
Model	PowerEdge R440	PowerEdge R440	PowerEdge R440	Dell PowerEdge R540
Form Factor	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives + LCD Bezel + 1 x 16x FH Riser	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives + LCD Bezel + 1 x 16x FH Riser	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives + LCD Bezel + 2 x 16x LP Riser	2U, 3.5" Chassis with up to 12 Hot Plug Hard Drives + LCD Bezel + Ready Rails™ Sliding Rails With Cable Management Arm + 1x16 FH, 3xLP PCI Slot
Processor	1 x Intel® Xeon® Silver 4110	1 x Intel® Xeon® Bronze 3106	2 x Intel® Xeon® Silver 4116	1 x Intel® Xeon® Silver 4110
Processor Speed /Core	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W)	1.7G, 8C/8T, 9.6GT/s 2UPI, 11M Cache, No Turbo, No HT (85W)	2.1G, 12C/24T, 9.6GT/s 2UPI, 16.5M Cache, Turbo, HT (85W)	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W) DDR4-2400
Memory	DDR4-2400, 16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank	8GB (1x8GB) RDIMM, 2666MT/s, Dual Rank	32GB (2x16GB) RDIMM, 2666MT/s, Dual Rank	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank
Network	Dual-Port 1GbE On-Board LOM	Dual-Port 1GbE On-Board LOM	Dual-Port 1GbE On-Board LOM	Dual-Port 1GbE On-Board LOM
Harddisk	2 x 1.2TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1TB 7.2K RPM NLSAS 12Gbps 512n 2.5in Hot-plug Hard Drive	4 x 1TB 7.2K RPM NLSAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1.2TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive, 3.5in HYB CARR
RAID Controller	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache
Optical Drive	DVD+/-RW, SATA	DVD+/-RW, SATA	DVD+/-RW, SATA	No Internal Optical Drive for 12 HD Chassis
Power Supply	Dual, Hot-plug, Redundant Power Supply (1+1), 550W	Dual, Hot-plug, Redundant Power Supply (1+1), 550W	Dual, Hot-plug, Redundant Power Supply (1+1), 550W	Dual, Hot-plug, Redundant Power Supply (1+1), 750W
System Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management
Warranty	3Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	133,750	107,000	208,650	139,100

Part Number	DEL-SnSR2401	DEL-SnSR2402	DEL-SnSR3401	DEL-SnSR3402
Model	DEL-SnSR2401	DEL-SnSR2402	Dell PowerEdge R340	Dell PowerEdge R340
Form Factor	3.5" Chassis with up to 4 Hot Plug Hard Drives, 1U/2U 2/4-Post Static Rails	3.5" Chassis with up to 4 Hot Plug Hard Drives, 1U/2U 2/4-Post Static Rails	3.5" Chassis with up to 4 Hot Plug Hard Drives, ReadyRails™ Sliding Rails With Cable Management Arm	3.5" Chassis with up to 4 Hot Plug Hard Drives, ReadyRails™ Sliding Rails With Cable Management Arm
Processor	Intel® Xeon® E-2124	Intel® Xeon® E-2124	Intel® Xeon® E-2124	Intel® Xeon® E-2124
Processor Speed / Core	3.3GHz, 8M cache, 4C/4T, turbo (71W)	3.3GHz, 8M cache, 4C/4T, turbo (71W)	3.3GHz, 8M cache, 4C/4T, turbo (71W)	3.3GHz, 8M cache, 4C/4T, turbo (71W)
Memory	8GB 2666MT/s DDR4 ECC UDIMM	8GB 2666MT/s DDR4 ECC UDIMM	8GB 2666MT/s DDR4 ECC UDIMM	8GB 2666MT/s DDR4 ECC UDIMM
Network	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM
Harddisk	1x BOSS controller card + with 1x M.2 Sticks 240G (No RAID),FH 2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-Plug Hard Drive	2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-Plug Hard Drive	1x BOSS controller card + with 1x M.2 Sticks 240G (No RAID),FH 2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-Plug Hard Drive	2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-Plug Hard Drive
RAID Controller	PERC H330 RAID Controller, Adapter, Full Height	PERC H330 RAID Controller, Adapter, Full Height	PERC H330 RAID Controller, Adapter, Full Height	PERC H330 RAID Controller, Adapter, Full Height
Optical Drive	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal
Power Supply	Single, Cabled Power Supply, 250W	Single, Cabled Power Supply, 250W	Dual, Hot-plug, Redundant Power Supply, 350W	Dual, Hot-plug, Redundant Power Supply, 350W
System Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	67,410	56,710	78,645	70,085

DELL PowerEdge : 2 Socket Rack Server



PowerEdge R640

Part Number	DEL-SNSR6404114	DEL-SNSR6404110	DEL-SNSR7403106
Model	PowerEdge R640	PowerEdge R640	PowerEdge R740
Form Factor	1U, Chassis with up to 10x2.5" Hard Drives, 2x16 LP PCI	1U, Chassis with up to 10x2.5" Hard Drives, 2x16 LP PCI	2U, Chassis with up to 16 x 2.5" Hard Drives, ReadyRail Sliding Rails With Cable Management Arm
Processor	1 x Intel® Xeon® Silver 4110	1 x Intel® Xeon® Silver 4110	1 x Intel® Xeon® Bronze 3104
Processor Speed / Core	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W) DDR4-2400	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W)	1.7G, 6C/6T, 9.6GT/s 2UPI, 8M Cache, No Turbo, No HT (85W)
Memory	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank	DDR4-2400	DDR4-2133
Network	Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC
Harddisk	2 x 600GB 15K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1.2TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 900GB 15K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive
RAID Controller	PERC H740P RAID Controller, 8Gb NV Cache, Minicard	PERC H730P RAID Controller, 2Gb NV Cache, Minicard	PERC H740P RAID Controller, 8Gb NV Cache, Minicard
Optical Drive	No Optical Drive	No Optical Drive	DVD+/-RW,SATA,Internal
Power Supply	Dual, Hot-plug, Redundant Power Supply (1+1), 750W	Dual, Hot-plug, Redundant Power Supply (1+1), 750W	Dual, Hot-plug, Redundant Power Supply (1+1), 750W
System Management	iDRAC9 Enterprise with OME Server Configuration Management, 2x 32GB microSDHC/SDXC Card	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management, 2x 32GB microSDHC/SDXC Card
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport and Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	167,883	144,450	141,133



PowerEdge R740

Part Number	DEL-SNSR7404112	DEL-SNSR7404110	DEL-SNSR7404114
Model	PowerEdge R740	PowerEdge R740	PowerEdge R740
Form Factor	2U, Chassis with up to 16 x 2.5" Hard Drives, ReadyRail Sliding Rails With Cable Management Arm	2U, Chassis with up to 16 x 2.5" Hard Drives + LCD Bezel, ReadyRail Sliding Rails With Cable Management Arm	2U, Chassis with up to 16 x 2.5" Hard Drives + LCD Bezel, ReadyRail Sliding Rails With Cable Management Arm
Processor	1 x Intel® Xeon® Silver 4112	1 x Intel® Xeon® Silver 4110	1 x Intel® Xeon® Silver 4114
Processor Speed / Core	2.6G, 4C/8T, 9.6GT/s 2UPI, 8.25M Cache, Turbo, HT (85W) DDR4-2400	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W) DDR4-2400	2.2G, 10C/20T, 9.6GT/s 2UPI, 14M Cache, Turbo, HT (85W)
Memory	32GB (2x16GB) RDIMM, 2666MT/s, Dual Rank	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank
Network	Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC	Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC	Broadcom 57416 2 Port 10Gb Base-T + 5720 2 Port 1Gb Base-T, rNDC
Harddisk	2 x 1.8TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1.2TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1.8TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive
RAID Controller	PERC H740P RAID Controller, 8Gb NV Cache, Minicard	PERC H730P RAID Controller, 2Gb NV Cache, Minicard	PERC H730P RAID Controller, 2Gb NV Cache, Minicard
Optical Drive	DVD+/-RW,SATA,Internal	DVD+/-RW,SATA,Internal	DVD+/-RW,SATA,Internal
Power Supply	Dual, Hot-plug, Redundant Power Supply (1+1), 750W	Dual, Hot-plug, Redundant Power Supply (1+1), 1100W	Dual, Hot-plug, Redundant Power Supply (1+1), 1100W
System Management	iDRAC9 Enterprise with OME Server Configuration Management, 2x 32GB microSDHC/SDXC Card	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management
Warranty	3Yr ProSupport and Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport and Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport and Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	181,900	146,590	165,850

Rack 2 CPU 1U & 2U



HPE ProLiant DL325 Gen10

HPE-P04647-B21



HPE ProLiant DL385 Gen10

HPE-878724-B21

Server HP มี Onsite Service ทุกคู่
สอบถามรายละเอียดโทร. 02-844-9622

CPU Types	AMD EPYC 7351 (2.4GHz/16-core/155-170W) Processor	2x AMD EPYC 7451 (2.3GHz/24-core/180W) Processor
CPU Min., max	1	Two processors
CPU L3 Cache	64 MB	64 MB
ECC Memory	16GB (2x8GB) DDR4-2666 Registered Smart Memory	64 GB RDIMM DR 2666 MT/s (2x 32 GB)
Graphic	Integrated Video Standard	Integrated Video Standard
PCI Slot	2-slots (x16, x8) as standard	3-slots (x8, x16, x8) as standard,
Harddisk	8 SFF Chassis	8 SFF Chassis
Onboard RAID	E208i-a	P408i-a w/Expander
Optical Drive	Optional: DVD-ROM, DVD-RW	DVD-RW
Total, Hotswap	8 SFF HDD Bays	8 SFF Chassis
Max, Internal disks	8 SFF Chassis	8 SFF Chassis
Interfaces	1 Rear VGA Port - Standard	
Onboard Gigabit Ethernet, Redundant Power	HPE 1Gb Ethernet 4-Port 331i Adapter plus	HPE 1Gb Ethernet 4-Port 331i Adapter plus
Dimensions (units)	(Height 4.29 x Width 43.46 x Depth 61.49 cm)	(Height 8.73 x Width 44.55 x Depth 67.94 cm)
Mechanical	rack 1U	rack 2U
Power Supply	HPE 500W Flex Slot Platinum Power Supply	2x 800W HPE FlexSlot power supply
OS Support	Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)	Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)
Warranty	3-year parts, 3-year labor, 3-year onsite support with next business day response 3/3/3	3-year parts, 3-year labor, 3-year onsite support with next business day response 3/3/3
SRP (inc. VAT)	129,470	332,600
	HPE-872479-B21 HPE 1.2TB X 2 UNIT	HPE-872479-B21 HPE 1.2TB X 2 UNIT



	HPE ProLiant DL360 Gen10 CLX P03630-B21	HPE ProLiant DL380 Gen10 CLX P02462-B21
Processor type	Silver 4208 2.1GHz 8-core 1P	Silver 4208 2.1GHz 8-core 1P
CPU Min.,Max	sausu Two processors	sausu Two processors
CPU L3 Cache	11 MB	11 MB
ECC Memory	16 GB RDIMM 2R 2933 MT/s(1x 16 GB)	16 GB RDIMM 2R 2933 MT/s(1x 16 GB)
Graphic	Integrated Video Standard	Integrated Video Standard
PCI Slot	2 PCIe: 1 x16 FH, 1 x8 LP	3-slots (x8, x16, x8 with dual m.2)
Hard Drives	8 SFF Chassis	8 SFF Chassis
Onboard Raid	P408i-a/2GB with Smart Storage Battery	P408i-a w/2GB cache
Optical drive	Not included (Optical Drive options available)	Not included (Optical Drive options available)
Total Hotswap	8 SFF HDD Bays	8 SFF Chassis
Max. # Internal Disks	8 SFF Chassis	8 SFF Chassis
Interface	1 Rear VGA Port - Standard	1 Rear VGA Port - Standard
Onboard Gigabit Ethernet	HPE 1Gb Ethernet 4-Port 331i Adapter plus	HPE 1Gb Ethernet 4-Port 331i Adapter plus
Dimension	(Height 4.29 x Width 43.46 x Depth 70.7 cm)	(Height 8.73 x Width 44.55 x Depth 67.94 cm)
Mechanical	1U rack	2U rack
Power Supply	1) HPE 500W Flex Slot Platinum Power Supply	1x HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit
OS Support	Microsoft Windows Server	Microsoft Windows Server
Warranty	Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)	Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)
Standard Warranty	3-year parts, 3-year labor, 3-year onsite support with next business day response 3/3/3	3-year parts, 3-year labor, 3-year onsite support with next business day response 3/3/3
SRP (inc. VAT)	141,454	145,306
	P09712-B21 HPE 480GB SATA MU SFF SC DS SSD X 3 UNIT	P09712-B21 HPE 480GB SATA MU SFF SC DS SSD X 3 UNIT

HPE Rack Server

Server HP มี Onsite Service ทุกกลุ่ม
สอบถามรายละเอียดโทร. 02-844-9622



HPE Proliant DL325 Gen10

HPE-P04647-B21

HPE Proliant DL325 Gen10

HPE-P04646-B21

HPE Proliant DL385 Gen10

HPE-878722-B21

CPU Types	AMD EPYC 7351 (2.4GHz/16-core/155-170W) Processor	AMD EPYC 7251 (2.1GHz/8-core/120W) Processor	2x AMD EPYC 7451 (2.3GHz/24-core/180W) Processor
CPU Min.,Max	1	1	Two processors
CPU L3 Cache	64MB	32MB	64MB
ECC Memory	16GB (2x8GB) DDR4-2666 Registered Smart Memory	8GB (1x8GB) DDR4-2666 Registered Smart Memory	64 GB RDIMM 2R 2666 MT/s (2x 32 GB)
Graphic	Integrated Video Standard	Integrated Video Standard	Integrated Video Standard
PCI Slot	2-slots (x16, x8) as standard	2-slots (x16, x8) as standard	3-slots (x8, x16, x8) as standard
Hard Drives	8 SFF Chassis	4 LFF Chassis	8 SFF Chassis
Onboard Raid	E208i-a	E208i-a	P408i-a
Optical drive	Optional: DVD-ROM, DVD-RW	Optional: DVD-ROM, DVD-RW	Universal Media Bay
Total Hotswap	8 SFF HDD Bays	4 LFF HDD Bays	8 SFF HDD Bays
Max.,internal Disks	8 SFF Chassis	4 LFF chassis	8 SFF Chassis
Interfaces	1 Rear VGA Port - Standard	1 Rear VGA Port - Standard	1 Rear VGA Port - Standard
Onboard Gigabit Ethernet	HPE 1Gb Ethernet 4-Port 331i Adapter plus	HPE 1Gb Ethernet 4-Port 331i Adapter plus	HPE 1Gb Ethernet 4-Port 331i Adapter plus
Dimension (units)	(Height 4.29 x Width 43.46 x Depth 61.49 cm)	(Height 4.29 x Width 43.46 x Depth 61.49 cm)	(Height 8.73 x Width 44.55 x Depth 67.94 cm)
Mechanical	rack 1U	rack 1U	rack 2U
Power Supply	HPE 500W Flex slot Platinum Power Supply	HPE 500W Flex slot Platinum Power Supply	2 x 800W HPE FlexSlot power supply
OS Support	"Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)"	"Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)"	"Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)"
Warranty	3-year parts, 3-year labor, 3-year onsite support with next business day response	3-year parts, 3-year labor, 3-year onsite support with next business day response	3-year parts, 3-year labor, 3-year onsite support with next business day response
SRP (inc. VAT)	129,470	93,000	320,200

HPE-872479-B21 HPE 1.2TB SAS HDD x 2 units

HPE-861681-B21 HPE 2TB SATA HDD x 2 units

HPE-872479-B21 HPE 1.2TB SAS 12G HDD x 2 units