

Acer Tower 1 Way Server Altos



* Service by Acer Care เฉพาะกรุงเทพฯ & ปริมณฑล นอกพื้นที่โปรดติดต่อฝ่ายขาย

	Altos T110 F5 ACR-USRJYST003	Altos T110 F5 ACR-USRJYST004	Altos T110 F5 ACR-USRJYST005
CPU Types	CPU Intel Core i3-9300 (3.7GHz up to 4.3GHz, 8M Cache)	Intel® Xeon® E-2224 Processor, 8M Cache, 3.40 GHz (4-core)	Intel® Xeon® E-2234 Processor 8M Cache, 3.60 GHz (4-core)
CPU max. support	1	1	1
Memory	8GB (1x8GB)	16GB (2x8GB)	8GB (1x8GB)
Memory max. support	Up to 4 x 2666/2400 MHz DDR4 unbuffered ECC memory	Up to 4 x 2666/2400 MHz DDR4 unbuffered ECC memory	Up to 4 x 2666/2400 MHz DDR4 unbuffered ECC memory
PCI Slots	1x PCI-E 3.0 x8 (in x16) 2x PCI-E 3.0 x4 (in x8) 1x M.2 2280/22110 slot (M-key, w/PCIe 3.0 x4)	1x PCI-E 3.0 x8 (in x16) 2x PCI-E 3.0 x4 (in x8) 1x M.2 2280/22110 slot (M-key, w/PCIe 3.0 x4)	1x PCI-E 3.0 x8 (in x16) 2x PCI-E 3.0 x4 (in x8) 1x M.2 2280/22110 slot (M-key, w/PCIe 3.0 x4)
Harddisk	2x 1TB 3.5" SATA 7200 RPM	2x 2TB 3.5" SATA 7200 RPM	2x 2TB 3.5" SATA 7200 RPM
Std. HDD Controller	Integrated SATA, Support S/W RAID 0,1,5,10 (Windows OS only)	Integrated SATA, Support S/W RAID 0,1,5,10 (Windows OS only)	Integrated SATA, Support S/W RAID 0,1,5,10 (Windows OS only)
H/W RAID Controller	-	-	-
Max. # Internal Disks supports	4 x 3.5" Non-Hot Plug bays for SATA HDD (or SAS HDD support limited to 2)	4 x 3.5" Non-Hot Plug bays for SATA HDD (or SAS HDD support limited to 2)	4 x 3.5" Non-Hot Plug bays for SATA HDD (or SAS HDD support limited to 2)
Optical device	DVDRW	DVDRW	DVDRW
Onboard Gigabit Ethernet	Yes, Single	Yes, Single	Yes, Single
Redundant Power Supply	No	No	No
Form Factor	Tower	Tower	Tower
OS Support	Microsoft® Windows Server® 2019 / 2016 Red Hat® Enterprise Linux®	Microsoft® Windows Server® 2019 / 2016 Red Hat® Enterprise Linux®	Microsoft® Windows Server® 2019 / 2016 Red Hat® Enterprise Linux®
Warranty	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand
SRP (inc. VAT)	26,400	31,700	29,100

Free bundle Keyboard and Mouse

Free bundle Keyboard and Mouse

Free bundle Keyboard and Mouse

Remark

- + By Order 45-60 days
- + Promotion(s) valid within July 1 - July 31, 2020 or Supplies Last!!!
- + VAT 7% is not included.
- + This promotion cannot be combined with any other promotions or special rates.
- + Acer reserves the right to add, modify, change, or discontinue this promotion and associated products without notice. All products are subject to availability, and all prices are subject to change without notice.
- + Above prices are landed in local currency (THB).
- * กรณีต้องการ upgrade สินค้า กรุณาติดต่อเอเซอร์ก่อนการสั่งซื้อทุกครั้ง เอเซอร์ขอสงวนสิทธิ์ในการรับผิดชอบกรณีลูกค้าสั่งซื้อสินค้าเอง หรือ ซื้อสินค้าภายนอก โดยมิได้ได้รับการยืนยัน

DELL PowerEdge : 1 Socket Tower Server

Part Number	DEL-SNST30PRO	DEL-SnST1401	DEL-SnST1402	DEL-SnST1403
Model	Dell PowerEdge T30	Dell PowerEdge T140	Dell PowerEdge T140	Dell PowerEdge T140
Form Factor	MiniTower Chassis with up to 4, 3.5" Cabled Hard Drives	3.5" Chassis up to 4 Cabled Hard Drives	3.5" Chassis up to 4 Cabled Hard Drives	3.5" Chassis up to 4 Cabled Hard Drives
Processor	Intel® Xeon® E3-1225v5	Intel® Xeon® E-2124	Intel® Xeon® E-2124	Intel® Xeon® E-2124
Processor Speed / Core	3.3GHz, 8MB Cache, 4Core/4T, Turbo, 80W	3.3GHz, 8M cache, 4C/4T, turbo (71W)	3.3GHz, 8M cache, 4C/4T, turbo (71W)	3.3GHz, 8M cache, 4C/4T, turbo (71W)
Memory	8GB DDR4 UDIMM, 2133 MT/s, ECC	8GB 2666MT/s DDR4 ECC UDIMM	8GB 2666MT/s DDR4 ECC UDIMM	8GB 2666MT/s DDR4 ECC UDIMM
Network	1 x Gigabit Ethernet	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM
Harddisk	1 x 1TB 7.2k Entry SATA 3.5 inch Cable	1x BOSS controller card + with 1x M.2 Sticks 240G (No RAID),FH 2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Cabled Hard Drive	2x 4TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Cabled Hard Drive	2x 1TB 7.2K RPM SATA 6Gbps 3.5in Cabled Hard Drive
RAID Controller	Intel Rapid Storage Controller 12.0	PERC H330 RAID Controller, Adapter, Full Height	PERC H330 RAID Controller, Adapter, Full Height	PERC H330 RAID Controller, Adapter, Full Height
Optical Drive	DVD+/- RW, SATA	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal
Power Supply	Single Cabled Power Supply, 290W	Single, Cabled Power Supply, 365W	Single, Cabled Power Supply, 365W	Single, Cabled Power Supply, 365W
System Management	NA	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management
Warranty	3Yr ProSupport: NBD Onsite Service	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	27,178	62,060	57,245	51,360

Part Number	DEL-SnST3401	DEL-SnST3402	DEL-SnST3403
Model	Dell PowerEdge T340	Dell PowerEdge T340	Dell PowerEdge T340
Form Factor	3.5" Chassis up to 8 Hot Plug Hard Drives	3.5" Chassis up to 8 Hot Plug Hard Drives	3.5" Chassis up to 8 Hot Plug Hard Drives
Processor	Intel® Xeon® E-2124	Intel® Xeon® E-2124	Intel® Xeon® E-2124
Processor Speed / Core	3.3GHz, 8M cache, 4C/4T, turbo (71W)	3.3GHz, 8M cache, 4C/4T, turbo (71W)	3.3GHz, 8M cache, 4C/4T, turbo (71W)
Memory	8GB 2666MT/s DDR4 ECC UDIMM	8GB 2666MT/s DDR4 ECC UDIMM	8GB 2666MT/s DDR4 ECC UDIMM
Network	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM
Harddisk	1x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive,3.5in HYB CARR AG 2x 8TB 7.2K RPM NLSAS 12Gbps 512e 3.5in Hot-plug Hard Drive	1x BOSS controller card + with 1x M.2 Sticks 240G (No RAID),FH 2x 4TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-plug Hard Drive	2x 2.4TB 10K RPM SAS 12Gbps 512e 2.5in Hot-plug Hard Drive, 3.5in HYB CARR
RAID Controller	PERC H330 RAID Controller, Adapter, Full Height	PERC H330 RAID Controller, Adapter, Full Height	PERC H330 RAID Controller, Adapter, Full Height
Optical Drive	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal
Power Supply	Dual, Hot-plug, Redundant Power Supply 1+1, 495W	Dual, Hot-plug, Redundant Power Supply 1+1, 495W	Dual, Hot-plug, Redundant Power Supply 1+1, 495W
System Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	78,110	69,550	67,410

DELL PowerEdge : 2 Socket Tower Server



Part Number	DEL-SNST4404110	DEL-SNST4403106	DEL-SNST6404110
Model	PowerEdge T440	PowerEdge T440	PowerEdge T640
Form Factor	Chassis with up to 8, 3.5" Hot Plug Hard Drives, Tower Configuration, Casters for PowerEdge Tower Chassis + Bezel	Chassis with up to 16 x2.5" Hot Plug Hard Drives, Tower Configuration, Casters for PowerEdge Tower Chassis + Bezel	Chassis with up to 18, 3.5" Hard Drives, Tower Configuration + Casters
Processor	1 x Intel® Xeon® Silver 4110	1 x Intel® Xeon® Bronze 3106	1 x Intel® Xeon® Silver 4110
Processor Speed / Core	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W) DDR4-2400	1.7G, 8C/8T, 9.6GT/s 2UPI, 11M Cache, No Turbo, No HT (85W) DDR4-2133	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W) DDR4-2400
Memory	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank	8GB (1x8GB) RDIMM, 2666MT/s, Dual Rank	16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank
Network	Dual-Port 1GbE On-Board LOM	Dual-Port 1GbE On-Board LOM	On-Board Dual-Port 10GbE LOM
Harddisk	2 x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-Plug Hard Drive	2 x 1TB 7.2K RPM NLSAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-Plug Hard Drive
RAID Controller	PERC H730P+ Adapter RAID Controller, 2Gb NV Cache	PERC H730P+ RAID Controller, 2GB NV Cache, Adapter, Full Height	PERC H730P+ Adapter RAID Controller, 2Gb NV Cache
Optical Drive	DVD +/-RW, SATA, Internal	DVD +/-RW, SATA, Internal	DVD +/-RW, SATA, Internal
Power Supply	Dual, Hot-plug, Redundant Power Supply (1+1), 1100W	Dual, Hot-plug, Redundant Power Supply (1+1), 750W	Dual, Hot-plug, Redundant Power Supply (1+1), 1100W
System Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	117,700	104,860	148,730
Disti SKUs	DEL-SNST4404116		
Model	PowerEdge T440		
Form Factor	Chassis with up to 16 x2.5" Hot Plug Hard Drives, Tower Configuration, Casters for PowerEdge Tower Chassis + Bezel		
Processor	2 x Intel® Xeon® Silver 4116		
Processor Speed / Core	2.1G, 12C/24T, 9.6GT/s 2UPI, 16.5M Cache, Turbo, HT (85W)		
Memory	16GB (2x16GB) RDIMM, 2666MT/s, Dual Rank		
Network	Dual-Port 1GbE On-Board LOM		
Harddisk	4 x 1TB 7.2K RPM NLSAS 12Gbps 512n 2.5in Hot-plug Hard Drive		
RAID Controller	PERC H730P+ RAID Controller, 2GB NV Cache, Adapter, Full Height		
Optical Drive	DVD +/-RW, SATA, Internal		
Power Supply	Dual, Hot-plug, Redundant Power Supply (1+1), 750W		
System Management	iDRAC9 Enterprise with OME Server Configuration Management		
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive		
SRP (inc. VAT)	203,300		



HPE Tower Server

Server HP มี Onsite Service ทั่วประเทศ
 สอบถามรายละเอียดโทร. 02-844-9622



HPE ProLiant ML30 Gen10

HPE-P06781-375

HPE ProLiant ML30 Gen10

HPE-P06789-375

CPU Types	Intel® Xeon® E-2124 (3.3GHz/4-core/8MB/71W) Processor	Intel® Xeon® E-2134 (3.5GHz/4-core/8MB/71W) Processor
CPU Min ,Max	รองรับ One Processors	รองรับ One Processors
CPU L3 Cache	8 MB	8 MB
ECC Memory	8GB (1x8GB UDIMMs, 2666 MT/s)	16GB (1x16GB UDIMMs, 2666 MT/s)
Graphic	Integrated Video Standard	Integrated Video Standard
PCI Slot	4 PCIe: 2 x16 FH, 2 x8 LP	4 PCIe: 2 x16 FH, 2 x8 LP
Hard Drives	4LFF Chassis	4LFF Chassis
Onboard Raid	Embedded S100i SW RAID with 4 SATA ports ** The S100i only supports Windows.	Embedded S100i SW RAID with 4 SATA ports ** The S100i only supports Windows.
Optical drive	Not included (Optical Drive options available)	Not included (Optical Drive options available)
Total Hotswap	4 LFF HDD Bays (Non Hot Plug)	4 LFF HDD Bays
Max,internal Disks	4LFF Chassis	4LFF Chassis
Interfaces	1 Rear VGA Port - Standard	1 Rear VGA Port - Standard
Onboard Gigabit Ethernet	HPE 1Gb 2-Port 332i Ethernet Adapter	HPE 1Gb 2-Port 332i Ethernet Adapter
Dimension (units)	(Height 36.83 x Width 17.50 x Depth 47.50 cm)	(Height 36.83 x Width 17.50 x Depth 47.50 cm)
Mechanical	4U Tower	4U Tower
Power Supply	1) 350W ATX Power Supply	1) HPE 500W Flex Slot Platinum Power Supply
OS Support	Microsoft Windows Server Red Hat Enterprise Linux (RHEL) SUSE Linux Enterprise Server (SLES)	Microsoft Windows Server Red Hat Enterprise Linux (RHEL) SUSE Linux Enterprise Server (SLES)
Warranty	HPE 3y FC NBD ML30 Gen10 SVC	HPE 3y FC NBD ML30 Gen10 SVC
SRP (inc. VAT)	29,900	79,500
Promotion	801882-B21 HPE 1TB SATA 7.2K LFF RW HDD	861683-B21 HPE 4TB SATA 7.2K LFF LP DS HDD x 2units

*สินค้ามีจำนวนจำกัด