KOLDTECH

STANDARD ITEMS

DISPLAY UNIT



Attractive counter top pastry display.

C-CT-R



Elegant counter top drop-in refrigerated display.

C-CT SERIES Counter Top Display Showcase

STANDARD FEATURES

Construction Tough, hygienic construction, with the choice of cold, warm or

ambient models to suit your application. Contemporary design with slanted front glass and light to visibly display your product.

Charcoal powder coated finish.

Glass ° Single pane glasses with slanted front glass for warm and

ambient display unit.

° Double glazed heat front glass. Single pane side glass for cold

display unit.

Body & Door Rear sliding single pane glass door. Back powder coated body.

Heated unit Heated unit is with removable water pan to keep product fresh

without excessive drying.

Ambient unit Same as hot display unit but without heater system. Display

product at ambient temperature.

Refrigerated unit Reliable, self-contained system, designed to drop in on top of the

> counter. Refrigerated model has condensing unit extended under the counter to maximise product display space. Fitted with condensate evaportor, no drain connection required. CFC free

R-404a refrigerant.

Controller Multi-function microprocessor controlled with digital

thermometer display.

Complete with 2 adjustable stainless steel wire shelves. Shelves

Optional extra Stainless steel exterior or choice of exterior powder coated paint

to enhance your store color profile. Square front glass instead of slanted. Rear double glazed reflective sliding door with mirror

film.

| TECHNICAL DATA | MODELS | | | |
|-----------------------------|--|-----------------|-----------------|------------------|
| MODEL NUMBER | C-CT-R8 | C-CT-A8 | C-CT-H8 | C-CT-H12 |
| Dimension - L x D x H (mm.) | 800 x 600 x 1265 | 800 x 600 x 815 | 800 x 600 x 815 | 1200 x 600 x 815 |
| Temperature range | 2 °C to 5 °C | Ambient | 35 °C to 80 °C | |
| Power suppy | 220 V / 50 Hz / 1 Ph (60 Hz models are available.) | | | |





