



ESC-3HC

ENVIRONMENTAL
STEAM CABINET

TRIPLE DOORS

Features



A Multiple chambers

2 small and 1 large chambers for steaming various dishes at the same time



B Timer alert and temperature display

Improved interface and alerting system for a precise control of steaming process



► Triple Door Version

Model: ESC-3HC

- Inner chamber dimension:
655 x 600 x 220 mm x 2nos
- Inner chamber dimension:
655 x 600 x 400 mm x 1nos
- 4 layers shelving

► Triple Door Version – Extra width

Model: ESC-3HX

- Inner chamber dimension:
955 x 600 x 220 mm x 2nos
- Inner chamber dimension:
955 x 600 x 400 mm x 1nos
- 4 layers shelving


Accessories & Options (p.30)

- Extra railways & S/S shelvings
- 5" heavy duty castors
- Flat base for plinth installation
- 17" rice pan
- CE and CSA version are available   

SPECIFICATIONS

Double Door - Vertical Open Door


ESC-2HC



Dimension	900 x 880 x 1765 mm H
Fuel	NG: DN20 ; LPG: DN20 ; TG: DN25
Water Inlet / Drainage	DN15 / DN40
Burner Ratings	42kW
Voltage	220V/5PH/50Hz ; 25W
Capacity	Equipped with 4 pairs of rail for shelves

Double Door - Horizontal Open Door


ESC-2VC



Dimension	800 x 880 x 1800 mm H
Fuel	NG: DN20 ; LPG: DN20 ; TG: DN25
Water Inlet / Drainage	DN15 / DN40
Burner Ratings	42kW
Voltage	220V/5PH/50Hz ; 25W
Capacity	Equipped with 4 pairs of rail for shelves

Triple Door


ESC-3HC



Dimension	900 x 880 x 1900 mm H
Fuel	NG: DN20 ; LPG: DN20 ; TG: DN25
Water Inlet / Drainage	DN15 / DN40
Burner Ratings	42kW
Voltage	220V/5PH/50Hz ; 25W
Capacity	Equipped with 4 pairs of rail for shelves

Triple Door - 1200 mm Width

ESC-3HX



Dimension	1200 x 880 x 1900 mm H
Fuel	NG: DN20 ; LPG: DN20 ; TG: DN25
Water Inlet / Drainage	DN15 / DN40
Burner Ratings	56kW
Voltage	220V/5PH/50Hz ; 25W
Capacity	Equipped with 4 pairs of rail for shelves